



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEx PRE 15.0021X**

Page 1 of 4

Certificate history:

Status: **Current**

Issue No: 5

Issue 4 (2019-10-23)

Issue 3 (2019-03-14)

Issue 2 (2018-02-14)

Issue 1 (2015-11-25)

Issue 0 (2015-10-20)

Date of Issue: 2020-05-08

Applicant: **ROXTEC INTERNATIONAL AB**
Box 540
SE-371 23 Karlskrona
Sweden

Equipment: **Cable Transit Device**

Optional accessory:

Type of Protection: **Ex eb, Ex tb**

Marking: Ex eb IIC Gb

Ex tb IIIC Db

Approved for issue on behalf of the IECEx
Certification Body:

Asle kaastad

Position:

Certification Manager

Signature:
(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

DNV GL Presafe AS
Veritasveien 3
1363 Høvik
Norway





IECEx Certificate of Conformity

Certificate No.: **IECEx PRE 15.0021X**

Page 2 of 4

Date of issue: 2020-05-08

Issue No: 5

Manufacturer: **ROXTEC INTERNATIONAL AB**
Box 540
SE-371 23 Karlskrona
Sweden

Additional manufacturing locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

IEC 60079-31:2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Edition:2

IEC 60079-7:2015 Explosive atmospheres – Part 7: Equipment protection by increased safety "e"
Edition:5.0

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

[NO/PRE/ExTR15.0060/00](#)
[NO/PRE/ExTR15.0060/03](#)

[NO/PRE/ExTR15.0060/01](#)
[NO/PRE/ExTR15.0060/04](#)

[NO/PRE/ExTR15.0060/02](#)
[NO/PRE/ExTR15.0060/05](#)

Quality Assessment Reports:

[SE/SP/QAR09.0001/05](#)

[SE/SP/QAR09.0001/06](#)



IECEx Certificate of Conformity

Certificate No.: **IECEx PRE 15.0021X**

Page 3 of 4

Date of issue: 2020-05-08

Issue No: 5

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The Cable Transit Devices 'CTDs'(see Type Designation below), for use with circular cables both armoured and non-armoured or corrugated cables (see Corrugated cables below) of non-interrupted and non-metallic outer jacket type or conduits. The CTDs consists of multi diameter sealing modules made of EPDM rubber (type CX and RMX as standard modules) and (type CX BG and RX BG B with bonding and grounding properties) that depending on each individual size, accepts a limited number of cable diameters in applicable types of frames made of stainless steel and shall be marked with the Ex symbol.

The modules are made of mirrored rubber profiles and each part has a number of thin rubber layers that are ending up with a core. The layers are made with two different colours to make the adaption to a cable exactly same on both halves and are allowed to differ one layer at most. To achieve appropriate sealing and mechanical properties to prevent the cables from slippage there shall always be a visible gap between the sealing module halves when adapting modules to the cable or conduit.

The correct sizes and procedure of assembling the cables to the modules are described in detail in the enclosed installation instructions. Ex Compression devices are used to achieve appropriate compression of the modules and solids.

The method to assemble the compression devices etc. and to achieve sealing of the CTDs is described in detail in the enclosed installation instructions. The CTDs installation instructions listed in this certificate will define each variant in detail and all applicable parts that are approved for use within that variant.

Type Designations:

HD 16 Ex HD 24 Ex, HD 32 Ex for use with CX- and CX BG modules.

HDLC Ex for use with RMX- and RX BG B modules.

Temperature Range:

-60°C to +80°C

Corrugated cables for use with: HD 16 Ex, HD 24 Ex, HD 32 Ex and HDLC Ex

ACIC (Armoured Control and Instrumentation Cable) according to C22.1-06 CEC,

ACWU (Armoured Cable for Wet locations) according to UL4,

TECK90 according to C22.2 No. 131-07

MC (Metal Clad) according to UL1569

SPECIFIC CONDITIONS OF USE: YES as shown below:

1. For maintaining the explosion protection, the installation instructions that accompany the products shall be considered.
2. Only cable for fixed installation is permitted for the cable transit device.
3. For optimum reliability wait 24 hours or longer after installation before exposing the cables/pipes to strain or pressure.



IECEx Certificate of Conformity

Certificate No.: **IECEx PRE 15.0021X**

Page 4 of 4

Date of issue: 2020-05-08

Issue No: 5

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

Update to new revision of EN IEC 60079-0. New model of core added, this new model is divided into two halves, one for each module half.