



| TYPE | APPLICABLE WITH CIRCULAR APERTURE | APPLICABLE WITH RECTANGULAR APERTURE |
|------------------|-----------------------------------|--------------------------------------|
| EzEntry 4/4 | YES | YES |
| EzEntry 4/9 | NO | YES |
| EzEntry 4 MINI/4 | YES | YES |
| EzEntry 4 MINI/9 | YES | YES |

| TYPE | Ø HOLE FOR SELF TAPPING SCREWS [mm] | Ø HOLE WHEN USING NUTS [mm] |
|----------------|-------------------------------------|-----------------------------|
| EzEntry 4 | 3.6 | 4.5 |
| EzEntry 4 MINI | 3.6 | 4.5 |

| | | | |
|-----|------------------|------------|-----------|
| C | LAYOUT CHANGED | 2024-10-21 | se-marfre |
| Rev | Type of revision | Date | Sign |

General tolerances used for manufacturing shown in document DOC-002180

Designed by/date: se-henols 2013-08-12
 Latest save date: 2024-10-24
 Format: A3
 Scale: 1 / 1
 Sheet no: 1 / 1
 TotWeight

Roxtec
www.roxtec.com

Title: APERTURE DIMENSIONS
EZENTRY 4 AND 4 MINI
 Restricted due to: Information drawing
 Drawing number: S1034803
 Projection method: Rev: C