



ITEM	QTY	Designation	Specification	Weight
11	1	INSTALLATION INSTRUCTION		
10	1	LUBRICANT	TALLOW	
9	4	STOP FLANGE 20x10x5 WOH AISI316	205556	0
8	10	SCREW	MC6S M6x80 A4	0
7	4	CORE Ø9	ROXYLON	0
6	1	REAR FITTING 2	ACID PROOF STAINLESS STEEL	0.1
5	2	REAR FITTING 1	ACID PROOF STAINLESS STEEL	0.1
4	1	FRONT FITTING 2	ACID PROOF STAINLESS STEEL	0.1
3	2	FRONT FITTING 1	ACID PROOF STAINLESS STEEL	0.1
2	1	RUBBER FRAME 2	ROXYLON	0.5
1	2	RUBBER FRAME 1	ROXYLON	0.3

General tolerances used for manufacturing shown in document DOC-002180		Designed by/date	Latest save date	Format	Scale	Sheet no	TotWeight
		se-larlar	2022-02-10	A3		1 / 1	1,8 kg
		Title H4 UG SEALS H4 125 UG				Projection method 	
Restricted due to www.roxtec.com		Information drawing			Drawing number S1576271		Rev D

D	LUBRICANT UPDATED.	2023-09-05	se-larlar
Rev	Type of revision	Date	Sign