




Roxtec C RS T seal

Round seal for single cable entries.

The Roxtec C RS T is a compact entry seal for single cables requiring a rating up to IP 69K. The seal is available with housing in stainless steel or nickel-plated brass. The cable transit device is available in four sizes to cover cables ranging from 3.6 to 30mm.



- Light-weight
- Allows pre-terminated cables

Product characteristics



IP/UL NEMA

Structure of installation



Cabinets & enclosures

Ratings & certificates

Tightness


- UL/NEMA 4,4X,12,13, IP 66/67 according to IEC 60529, IP 69K according to IEC 60529 / ISO 20653

Sealing components

Sealing components



Lubricant




C RS T kit

For detailed information, please visit [roxtec.com](https://www.roxtec.com).



Pre-configured transit kits

in/lbs



Product	Configuration	Aperture dimensions Ø	Weight	Art. no
C RS T 25 AISI316	1x (0.142-0.472)	1.299 - 1.299	0.24	104761
C RS T 31 AISI316	1x (0.157-0.669)	1.614 - 1.614	0.35	5CRST00011494
C RS T 43 AISI316	1x (0.157-0.906)	2.047 - 2.047	0.84	106064
C RS T 50 AISI316	1x (0.315-1.181)	2.52 - 2.52	1.43	106065
C RS T 25	1x (0.142-0.472)	1.299 - 1.299	0.22	CRST010025046
C RS T 31	1x (0.157-0.669)	1.614 - 1.614	0.35	CRST010031046
C RS T 43	1x (0.157-0.906)	2.047 - 2.047	0.86	CRST010043046
C RS T 50	1x (0.315-1.181)	2.52 - 2.52	1.46	CRST010050046

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2026-08-11