



Pasamuros Roxtec CF 16 Ex

Dispositivo de paso para instalaciones en zonas explosivas con marco de metal de perfil bajo.

El Roxtec CF 16 Ex es un sello de entrada de cables de perfil bajo para envolventes de armarios. El dispositivo de paso está certificado para el uso en zonas Ex e y Ex tb. El sello está disponible en versión de acero inoxidable 304 y en versión que se puede abrir para cables ya instalados, así como, dispone de una versión para aplicaciones EMC.



- Resistente a roedores
- Eficiencia de área
- Permite cables precabados

Características del producto



IP/UL NEMA



Clasificación Ex

Estructura de instalación



Armarios
envolventes
&
prefabricad
os

Tipo de montaje



Atornilladura

Calificaciones y certificados

Estanquidad

- IP 66/67, UL/NEMA 4,4X,12,13

Soportes

- Clasificación Ex

Dimensiones del marco


mm/kg

Las variantes de marcos que figuran a continuación son una selección limitada. Para ver la gama completa de marcos y configuraciones, visite [roxtec.com](https://www.roxtec.com).

Título	Aperturas de marcos	Espacio útil de sellado	Dimensiones externas WxHxD	Dimensiones de abertura w x h	Peso	N.º de art.
CF 16 Ex	1	40 x 160	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	EXCSF0000160010
CF 16 Ex AISI304	1	40 x 160	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.2	EXCSF0000160021

Datos de los componentes de sellado

Componentes de sellado



Módulo CM Ex con Multidiameter™



Módulo de compensación sólido CM Ex



Lubricante Roxtec

Para obtener información detallada, visite [roxtec.com](https://www.roxtec.com).



Kits de sellos preconfigurados

mm/kg

Título	Configuración	Dimensiones externas WxHxD	Dimensiones de abertura w x h	Peso	N.º de art.
CF 16/4 Ex AISI304	4x (9.5-32.5)			1.6	EXECF16000421
CF 16/10 Ex AISI304	2x (9.5-32.5), 8x (3.5-16.5)			1	EXECF16001021
CF 16/16 Ex AISI304	16x (3.5-16.5)			1.6	EXECF16001621
CF 16/19 Ex AISI304	6x (3.5-16.5), 12x (3.5-10.5), 1x (9.5-32.5)			1.6	EXECF16001921

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-03-30