



Roxtec CF 16 Ex doorvoering

Doorvoerunit voor Ex-toepassingen met een ondiep ontwerp met metalen frame.

De Roxtec CF 16 Ex is een ondiepe kabelafdichting voor behuizingen. De doorvoerunit is gecertificeerd voor gebruik in Ex e- en Ex tb-toepassingen. De afdichting is verkrijgbaar in roestvast staal (304) en te openen versies, en versies voor EMC-toepassingen.



- Knaagdierbestendig
- Ruimtebesparend
- Geschikt voor kabels met connector

Producteigenschappen



IP/UL NEMA



Ex-geclassificeerd

Installatiestructuur



Kasten en behuizingen

Montagetype



Bouten

Specificaties en certificaten

Dichtheid

- IP 66/67, UL/NEMA 4,4X,12,13

Supports

- Ex-geclassificeerd

Afmetingen frame


mm/kg

De onderstaande frame-uitvoeringen zijn een beperkte selectie. Ga naar [roxtec.com](https://www.roxtec.com) voor het volledige assortiment frames en configuraties.

Titel	Frame-openingen	Vrije doorvoerruimte	Buitenafmetingen WxHxD	Afmetingen opening w x h	Gewicht	Art. nr.
CF 16 Ex	1	40 x 160	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.4	EXCSF0000160010
CF 16 Ex AISI304	1	40 x 160	93 x 234 x 42	71(+1/-1) x 187(+2/-0.5)	1.2	EXCSF0000160021

Gegevens van afdichtcomponenten

Afdichtcomponenten



CM Ex module met Multidiameter™



Massieve CM Ex compensatiemodule



vetstick

Ga naar [roxtec.com](https://www.roxtec.com) voor uitgebreide informatie.



Vooraf geconfigureerde doorvoersets

mm/kg

Titel	Configuratie	Buitenafmetingen WxHxD	Afmetingen opening w x h	Gewicht	Art. nr.
CF 16/4 Ex AISI304	4x (9.5-32.5)			1.6	EXECF16000421
CF 16/10 Ex AISI304	2x (9.5-32.5), 8x (3.5-16.5)			1	EXECF16001021
CF 16/16 Ex AISI304	16x (3.5-16.5)			1.6	EXECF16001621
CF 16/19 Ex AISI304	6x (3.5-16.5), 12x (3.5-10.5), 1x (9.5-32.5)			1.6	EXECF16001921

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-03-30