



Roxtec HD Ex -läpiviennit

Korkeatiheyksiset läpiviennit 316L-teräskehysellä Ex-alueille.

Roxtec HD Ex -kaapeliläpiviennit on tarkoitettu ankariin ja vaarallisiin olosuhteisiin. Kolmessa eri koossa saatavat läpiviennit on sertifioitu Ex eb- ja Ex tb -alueille -60--80°C lämpötiloihin. Ne ovat tilatehokkaita ja niihin voidaan asentaa jopa 32 kaapelia aukkoa kohden. Läpivientitiivisteissä on 316L-teräskehys ja tiivistysmoduulit, jotka sopivat erikokoisille kaapeleille. Tiivistettä voi käyttää armeerattuihin kaapeleihin, jotka vaativat potentiaalintasausta ja maadoitusta.



- Korroosiosuojattu
- Kevyt
- Tilatehokas

Tuotteen ominaisuudet



IP/UL NEMA



Ex-luokiteltu



Sähköturvallisuus

Asennusrakenne



Kaapit ja kotelot

Asennustyyppi



Pulttaus

Luokitukset ja sertifioinnit

Tiiviyys

- IP 66/67, UL/NEMA 4,4X,12,13

Tuki

- Potentiaalintasausta ja maadoitus
- Ex-luokiteltu

Kehyksen mitat

mm/kg

Alla olevat kehysvaihtoehdot ovat vain osa valikoimastamme. Kattava valikoima kehyksiä ja kokoonpanoja löytyy osoitteesta [roxtec.com](https://www.roxtec.com).


Otsikko	Kehysaukot	Pakkaustila	Ulkomitat WxHxD	Aukon mitat w x h	Paino	Tuotenumero
HD 16 Ex FRAME ASSEMBLY	1	40 x 160	83,8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	1.6	193085
HD 32 Ex FRAME ASSEMBLY	2	40 x 160	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	2.3	152499

Tiivistyskomponenttien tiedot

Tiivistyskomponentit



CX Multidiameter™ -moduulit



CX BG™ Multidiameter™ -moduulit



Roxtec-asennusgeeli Ex

Lisätietoja on osoitteessa [roxtec.com](https://www.roxtec.com).



Valmiiksi määritetyt läpivientisarjat

mm/kg



HD 16/4 BG Ex



HDLC/24+2 Ex



HDLC/24+2 BG Ex



HD 16/4 Ex



HD 16/10 Ex



HD 16/16 Ex



HD 16/16 BG Ex



HD 32/8 Ex



HD 32/20 Ex



HD 32/32 Ex



HD 32/8 BG Ex



HD 32/20 BG Ex



HD 32/32 BG Ex



HD 16/10 BG Ex

Otsikko	Kokoonpano	Ulkomitat WxHxD	Aukon mitat w x h	Paino	Tuotenro
HD 16/4 BG Ex	4x (9.5-31.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193107
HDLC/24+2 Ex	2x (24.0-52.0), 24x (4.0-15.5)	378 x 120 x 94	366(+1/-1) x 108(+1/-1)	6.2	173275
HDLC/24+2 BG Ex	2x (24.0-52.0), 24x (4.0-15.5)	378 x 120 x 94	366(+1/-1) x 108(+1/-1)	6.3	173282
HD 16/4 Ex	4x (9.5-31.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193103
HD 16/10 Ex	2x (9.5-31.5), 8x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	198298
HD 16/16 Ex	16x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193102
HD 16/16 BG Ex	16x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193106
HD 32/8 Ex	8x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165191
HD 32/20 Ex	16x (4.0-15.5), 4x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165193
HD 32/32 Ex	32x (4.0-15.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165194
HD 32/8 BG Ex	8x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165195
HD 32/20 BG Ex	4x (9.5-31.5), 16x (4.0-15.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165196
HD 32/32 BG Ex	32x (4.0-15.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165197
HD 16/10 BG Ex	2x (9.5-31.5), 8x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2.1	198300

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-19