



Passages Roxtec HD Ex

Passages une pour forte densité de câbles, avec un cadre en inox 316L, pour les environnements Atex.

Les Roxtec HD Ex sont des passages de câbles pour les environnements difficiles et dangereux. Ils sont certifiés pour les zones Ex eb et Ex tb, à des températures de -60 à +80°C, et sont disponibles en trois tailles différentes. Les passages de câbles permettent d'optimiser l'espace et peuvent accueillir jusqu'à 32 câbles par ouverture. Les passages étanches sont composés d'un cadre en acier inoxydable 316L et de modules d'étanchéité qui s'adaptent à différentes tailles de câbles. La solution peut être utilisée avec des câbles armés nécessitant une liaison et une mise à la terre.



- Résistant à la corrosion
- Léger
- Surface optimisée

Caractéristiques du produit



IP/UL NEMA



Certifié Atex



Sécurité électrique

Structure d'installation



Armoires et coffrets

Type de fixation



Boulonnage

Classements et certificats

Étanchéité

- IP 66/67, UL/NEMA 4,4X,12,13

Supports

- Liaison et mise à la terre
- Certifié Atex

Dimensions du cadre

mm/kg

Les variantes de cadre ci-dessous sont une sélection limitée. Pour voir la gamme complète de cadres et de configurations, veuillez visiter [roxtec.com](https://www.roxtec.com).

Titre	Ouvertures de cadre	Espace de remplissage	Dimensions externes WxHxD	Dimensions d'ouverture w x h	Poids	N° art.
HD 16 Ex FRAME ASSEMBLY	1	40 x 160	83,8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	1.6	193085
HD 32 Ex FRAME ASSEMBLY	2	40 x 160	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	2.3	152499

Éléments d'étanchéité

Éléments d'étanchéité



Modules CX avec Multidiameter™



Modules CX BG™ avec Multidiameter™



Gel d'assemblage Ex

Pour plus d'informations, veuillez consulter [roxtec.com](https://www.roxtec.com).



Kits de passage préconfigurés

mm/kg



HD 16/4 BG Ex



HDLC/24+2 Ex



HDLC/24+2 BG Ex



HD 16/4 Ex



HD 16/10 Ex



HD 16/16 Ex



HD 16/16 BG Ex



HD 32/8 Ex



HD 32/20 Ex



HD 32/32 Ex



HD 32/8 BG Ex



HD 32/20 BG Ex



HD 32/32 BG Ex



HD 16/10 BG Ex

Titre	Configuration	Dimensions externes WxHxD	Dimensions d'ouverture w x h	Poids	N° art.
HD 16/4 BG Ex	4x (9.5-31.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193107
HDLC/24+2 Ex	2x (24.0-52.0), 24x (4.0-15.5)	378 x 120 x 94	366(+1/-1) x 108(+1/-1)	6.2	173275
HDLC/24+2 BG Ex	2x (24.0-52.0), 24x (4.0-15.5)	378 x 120 x 94	366(+1/-1) x 108(+1/-1)	6.3	173282
HD 16/4 Ex	4x (9.5-31.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193103
HD 16/10 Ex	2x (9.5-31.5), 8x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	198298
HD 16/16 Ex	16x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193102
HD 16/16 BG Ex	16x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193106
HD 32/8 Ex	8x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165191
HD 32/20 Ex	16x (4.0-15.5), 4x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165193
HD 32/32 Ex	32x (4.0-15.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165194
HD 32/8 BG Ex	8x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165195
HD 32/20 BG Ex	4x (9.5-31.5), 16x (4.0-15.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165196
HD 32/32 BG Ex	32x (4.0-15.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165197
HD 16/10 BG Ex	2x (9.5-31.5), 8x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2.1	198300

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-17