



Roxtec HD Ex 穿隔系统

带 316L 框架的高电缆密度穿隔系统可用于 Ex 环境。

Roxtec HD Ex 是用于恶劣和危险环境的电缆穿隔系统。经认证可用于 Ex eb 和 Ex tb 区域于工作温度为 -60 到 +80°C 并提供三种不同的尺寸。该电缆穿隔非常节省空间于每个开孔可允许有多达 32 条电缆。该密封系统配有 316L 不锈钢框架于以及可灵活适配各种电缆规格的密封模块。该密封系统可与需要接地的铠装电缆配合使用。



- 耐腐蚀
- 轻型
- 节省空间

产品特性



IP/UL NEMA



防爆等级



电气安全

安装结构



箱柜和机柜

等级和证书

密封性

- 符合 IEC 60529 标准 IP 66/67 防护等级, UL/NEMA 4,4X,12,13

支持

- 连接和接地
- 防爆等级

框架尺寸

mm/kg

下方的不同框架只是部分选择。要了解全部的框架和配置于请访问 [roxtec.com](https://www.roxtec.com)。

标题	框架开口	密封空间	外部尺寸 WxHxD	开孔尺寸 w x h	重量	产品编号
HD 16 Ex FRAME ASSEMBLY	1	40 x 160	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	1.6	193085
HD 32 Ex FRAME ASSEMBLY	2	40 x 160	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	2.3	152499

密封组件数据

密封组件



Multidiameter™ V 多径 V-CX 模块



Ex 安装凝胶



Multidiameter™ V 多径 V-CX BG™ 模块

如需了解详细信息于请访问 [roxtec.com](https://www.roxtec.com)。



预装配的穿隔套件

mm/kg



标题	配置	外部尺寸 WxHxD	开孔尺寸 w x h	重量	产品编号
HD 16/4 BG Ex	4x (9.5-31.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193107
HD 16/4 Ex	4x (9.5-31.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193103
HD 16/10 BG Ex	2x (9.5-31.5), 8x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2.1	198300
HD 16/16 BG Ex	16x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193106
HD 16/10 Ex	2x (9.5-31.5), 8x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	198298
HD 16/16 Ex	16x (4.0-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	2	193102
HD 32/8 BG Ex	8x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165195
HD 32/8 Ex	8x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165191
HD 32/20 BG Ex	4x (9.5-31.5), 16x (4.0-15.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165196
HD 32/20 Ex	16x (4.0-15.5), 4x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165193
HD 32/32 BG Ex	32x (4.0-15.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165197
HD 32/32 Ex	32x (4.0-15.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	165194
HDLC/24+2 BG Ex	2x (24.0-52.0), 24x (4.0-15.5)	378 x 120 x 94	366(+1/-1) x 108(+1/-1)	6.3	173282
HDLC/24+2 Ex	2x (24.0-52.0), 24x (4.0-15.5)	378 x 120 x 94	366(+1/-1) x 108(+1/-1)	6.2	173275

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-07-03