






Roxtec GH BG™ 穿隔系统

带法兰和接地端子的穿隔系统チ适用于栓接到平整的结构上。

Roxtec GH BG™ 是一种用于接地应用的电缆和管道密封系统。 其矩形钢制框架可栓接到钢 制或夹心墙/地板上チ可允许高电缆和管道密封密度。 该穿隔系统可与镀锌钢 GE 扩 展型框架配合使用チ以适配较厚墙体的厚度。 Roxtec ECソ电气连续性ゾ检测条可用于帮 助指示穿隔装置的电气性能。







易于维护和检查

产品特性









安装结构









箱柜和机柜

等级和证书

火灾

● E/EI 等级符合 EN 13501

● F/T 等级符合 UL 1479

密封性

气体: 0.1 barソ洪灾ゾ


● 符合 IEC 60529 标准 IP 66/67 防护等级

支持

● 连接和接地

框架尺寸

下方的不同框架只是部分选择。 要了解全部的框架和配置チ请访问 roxtec.com。



标题	框架开口	密封空间	外部尺寸 WxHxD	开孔尺寸 w x h	重量	产品编号
GH BG 6x1 GALV	1	120 x 180	252.5 x 350 x 93.6	148(+5/-5) x 245(+5/-5)	4.4	109604
GH BG 6x2 GALV	2	120 x 180	383 x 350 x 93.6	278(+5/-5) x 245(+5/-5)	7.5	110003
GH BG 6x3 GALV	3	120 x 180	513.5 x 350 x 93.6	409(+5/-5) x 245(+5/-5)	10.4	110015
GH BG 6x1 AISI316	1	120 x 180	252.5 x 350 x 93.6	148(+5/-5) x 245(+5/-5)	4.9	122511
GH BG 6x2 AISI316	2	120 x 180	383 x 350 x 93.6	278(+5/-5) x 245(+5/-5)	6.7	122512
GH BG 6x3 AISI316	3	120 x 180	513.5 x 350 x 93.6	409(+5/-5) x 245(+5/-5)	9.9	110477





https://www.roxtec.com/linktransit/zh-cn/solution/1100



密封组件数据

密封组件







RM BG™ 盲堵模块



BG™ 密封套件



隔层板



润滑脂





GE 扩展型框架



支架工具



楔形压紧件和楔形压紧套件

如需了解详细信息チ请访问 roxtec.com。



配件 ES 和 BG

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-07-03



Roxtec ® and Multidiameter ® are registered trademarks of Roxtec in Sweden and/or other countries.

2025-07-03