



Roxtec GH FL100 트랜짓

균일하지 않은 구조물에 볼트로 장착할 수 있는 광폭 플랜지를 갖춘 트랜짓

Roxtec GH FL100은 고밀도 모듈 설치가 가능한 케이블 및 파이프 씰입니다. 관통 장치는 콘크리트 또는 벽돌 벽/바닥에 볼트로 고정할 때 단단한 씰링을 보장합니다. 직사각형 강철 프레임에는 100mm 너비의 플랜지가 있어 균열 위험을 피하기 위해 벽의 개구부에서 볼트 구멍을 더 멀리 배치할 수 있습니다. 이 트랜짓은 아연 도금된 강철 재질의 GE 확장 프레임과 함께 사용하여 두꺼운 벽에도 사용 가능합니다.

- 설치류 차단
- 공간 효율성
- 유지 및 검사 용이

제품 특징점



내화



IP/UL NEMA

설치 구조



콘크리트



벽돌

장착 유형



볼트체결

등급 및 인증

화재

- EN 13501에 따른 E/EI 등급
- UL 1479에 따른 F/T 등급

강도

- IP 66/67

프레임 치수

mm/kg

아래의 프레임 변화는 제한된 선택입니다. 프레임 및 구성의 전체 범위를 보려면 [roxtec.com](https://www.roxtec.com)을 방문하십시오.

구성	프레임 입구	모듈설치공간	외부 치수 WxHxD	홀 치수 w x h	무게	Art. 번호
GH 6x1 FL100 GALV	1	120 x 180	332.5 x 430 x 60	148(+5/-5) x 245(+5/-5)	7.8	122158
GH 6x2 FL100 GALV	2	120 x 180	463 x 430 x 60	278(+5/-5) x 245(+5/-5)	11	122159
GH 6x3 FL100 GALV	3	120 x 180	593.5 x 430 x 60	409(+5/-5) x 245(+5/-5)	13.8	122160
GH 6x1 FL100 AISI316	1	120 x 180	332.5 x 430 x 60	148(+5/-5) x 245(+5/-5)	7.4	105508
GH 6x2 FL100 AISI316	2	120 x 180	463 x 430 x 60	278(+5/-5) x 245(+5/-5)	10.5	120984
GH 6x3 FL100 AISI316	3	120 x 180	593.5 x 430 x 60	409(+5/-5) x 245(+5/-5)	13	105509



씰링 컴포넌트 데이터


씰링 컴포넌트




윤활제




Wedge 및 We



RM 모듈(Mult idiameter™)



RM 솔리드 모듈



스테이플레이트



GE 확장 프레임



홀더 도구



씰링 키트

액세서리

자세한 내용은 [roxtec.com](https://www.roxtec.com)을 방문하십시오.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.
 Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.
 Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.
 The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>
 We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.
 This document was generated on: 2024-04-09