



# Etanșare Roxtec H3 UG™

Soluție pentru cabluri care intră prin fundații.

Etanșarea Roxtec H3 UG™ este ideală pentru cabluri care intră prin fundații și funcționează ca o barieră de lungă durată împotriva inundațiilor, gazelor, umidității și rozătoarelor. Este o etanșare din trei părți, ușor de instalat atât în condiții de umiditate cât și în prezența apei. Soluția rezistă la o îndoire extremă a cablurilor și are o toleranță de +3 mm spre exterior, precum și un indicator care arată când se obține o compresie optimă. Etanșarea poate fi instalată în manșoane, țevi sau găuri carotate.



- Rezistent la rozătoare
- Rapid și ușor de instalat
- Asigură o fixare excelentă a cablurilor

## Caracteristicile produsului



Etanșă la apă



Etanșă la gaze



IP/UL NEMA

## Structura instalației



Beton

## Tip de montaj



Gol existent



Piesă de trecere existentă

## Clase și certificate

### Etanșeitate

- Gaz: 0,3 bari (constantă)
- Apă: 0,3 bari (constantă)
- IP 68

## Date componente de etanșare

### Componente de etanșare



Etanșare H3 UG™



Lubrifiant Roxtec

Pentru mai multe informații, vă rugăm să vizitați [roxtec.com](https://www.roxtec.com).



## Kituri de treceri preconfigurate

mm/kg



H3-135 UG




H3-150 UG



H3-185 UG



H3-200 UG



H3-135 UG WOC



H3-150 UG WOC



H3-185 UG WOC

Titlu	Configurație	Dimensiuni deschidere Ø	Greutate	Nr. art.
H3-135 UG	3x (23.0-43.0)	135 - 138	2.2	126281
H3-150 UG	3x (24.0-52.0)	150 - 153	2.5	151561
H3-185 UG	3x (48.0-64.0)	185 - 188	3.9	126283
H3-200 UG	3x (48.0-68.0)	200 - 203	4.3	117842
H3-135 UG WOC	3x (23.0-43.0)	135 - 138	2.3	151306
H3-150 UG WOC	3x (24.0-52.0)	150 - 153	2.6	155188
H3-185 UG WOC	3x (48.0-64.0)	185 - 188	3.5	151308
H3-200 UG WOC	3x (48.0-68.0)	200 - 203	4	108697
H3-150 UG INSERTABLE	3x (24.0-52.0)	150 - 153	2.6	155189
H3-200 UG INSERTABLE	3x (48.0-68.0)	200 - 203	4.4	127053
H3-150 UG INSERTABLE WOC	3x (24.0-52.0)	150 - 153	2.3	166396
H3-200 UG INSERTABLE WOC	3x (48.0-68.0)	200 - 203	3.7	164807

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-03-22