



# **Roxtec R UG™ transit**

Transit in flexible configuration for multiple cables and pipes entering via foundations.

The Roxtec R  $UG^{\scriptscriptstyle\mathsf{TM}}$  is a transit for multiple cables and pipes entering via foundations. The seal allows for a mix of small and large cables and pipes in the same opening and works as a long-lasting barrier against flooding, gas, humidity and rodents. The transit withstands extreme cable bending and can be installed into sleeves, conduits and core drilled holes also in wet conditions and environments with running water.





- Rodent resistant
- Area efficient
- Quick and easy to install
- Easy to maintain and inspect

#### **Product characteristics**







Watertiaht

IP/UL NEMA

### Structure of installation



### Mounting type







# **Ratings & certificates**

### **Tightness**

- Gas: 0.3 bar (constant)
- Water: 0.3 bar (constant)

### **Frame dimensions**

### mm/kg

The frame variants below are a limited selection. For the full range of frames and configurations, please visit roxtec.com.

Product	Packing space	Aperture dimensions $\varnothing$	Weight	Art. no
R 100 UG	60 x 60	100 - 102	0.8	156872
R 150 UG	90 x 90	150 - 152	1.9	108693
R 200 UG	120 x 120	200 - 202	3.1	108698

# **Sealing components**

### **Sealing components**





RM UG™ module with Multidiameter™

Lubricant

For detailed information, please visit roxtec.com.

2024-04-27





## **Pre-configured transit kits**

### mm/kg



Product	Configuration	Aperture dimensions ∅	Weight	Art. no
R 150/9 UG	9x (10.0-23.5)		2.8	117821
R 200/4 UG	4x (24.0-52.0)		4.5	117822
R 200/7 UG	3x (24.0-52.0), 4x (10.0-23.5)	200 - 202	4.5	117854
R 200/15 UG	7x (9.5-31.0), 8x (4.0-13.0)		4.5	117855
R 150/6 UG	5x (10.0-23.5), 1x (24.0-52.0)		2.6	120859
R 100/4 UG	4x (10.0-23.5)		1.2	156874
R 100/6 UG	1x (4.0-13.0), 4x (4.0-13.0), 1x (9.5-31.0)		1.2	156875

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-27

2/2 2024-04-27