



# Roxtec R UG™ doorvoer

Doorvoer in flexibele configuratie voor meerdere kabels en leidingen die binnenkomen via funderingen.

De Roxtec R UG™ is een doorvoer voor meerdere kabels en leidingen die binnenkomen via funderingen. De afdichting is geschikt voor de doorvoering van een combinatie van kleine en grote kabels en leidingen in dezelfde opening, en biedt bescherming tegen wateroverlast, gas, vocht en knaagdieren. De doorvoer is bestand tegen extreme kabelbuigkrachten en kan worden geïnstalleerd in mantelbuizen, leidingen en voorgeboorde openingen, ook in natte omstandigheden en omgevingen met stromend water.



- Knaagdierbestendig
- Ruimtebesparend
- Snel en eenvoudig te installeren
- Eenvoudig te onderhouden en inspecteren

## Producteigenschappen



Waterdicht



Gasdicht



IP/UL NEMA

## Installatiestructuur



Beton

## Montagetype



Bestaande opening



Bestaande buis

## Specificaties en certificaten

### Dichtheid

- Gas: 0,3 bar (constante druk)
- Water: 0,3 bar (constante druk)
- IP 68

## Afmetingen frame

mm/kg

De onderstaande frame-uitvoeringen zijn een beperkte selectie. Ga naar [roxtec.com](https://www.roxtec.com) voor het volledige assortiment frames en configuraties.

Titel	Vrije doorvoerruimte	Afmetingen opening Ø	Gewicht	Art. nr.
R 100 UG	60 x 60	100 - 102	0.8	156872
R 150 UG	90 x 90	150 - 152	1.9	108693
R 200 UG	120 x 120	200 - 202	3.1	108698

## Gegevens van afdichtcomponenten

### Afdichtcomponenten



RM UG™ module met Multidiameter™



vetstick

Ga naar [roxtec.com](https://www.roxtec.com) voor uitgebreide informatie.



# Vooraf geconfigureerde doorvoersets

mm/kg



Titel	Configuratie	Afmetingen opening Ø	Gewicht	Art. nr.
R 150/9 UG	9x (10.0-23.5)		2.8	117821
R 200/4 UG	4x (24.0-52.0)		4.5	117822
R 200/7 UG	3x (24.0-52.0), 4x (10.0-23.5)	200 - 202	4.5	117854
R 200/15 UG	7x (9.5-31.0), 8x (4.0-13.0)		4.5	117855
R 150/6 UG	5x (10.0-23.5), 1x (24.0-52.0)		2.6	120859
R 100/4 UG	4x (10.0-23.5)		1.2	156874
R 100/6 UG	1x (4.0-13.0), 4x (4.0-13.0), 1x (9.5-31.0)		1.2	156875

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-03-22