






# **Roxtec RS seal**

The Roxtec RS is a seal for single cables or pipes in metal sleeves or existing holes. The entry seal has two halves with removable layers making it adaptable to cables and pipes of different sizes. The design of the transit makes it easy to install around existing cables or pipes.





#### Rodent resistant

### Quick and easy to install

#### **Product characteristics**







Structure of installation





Mounting type





Existing hole

Existing sleeve

### **Ratings & certificates**

#### Fire

- A-CLASS according to IMO 2010 FTP Code
- E/EI rating according to EN 13501
- E/EI rating according to EN 45545 E30
- F/T rating according to UL 1479
- H-CLASS according to IMO 2010 FTP Code + HC fire load curve
- Jet fire according to ISO 22899-1 and OTI 95634


#### **Tightness**

- Gas: 2.67 bar (catastrophic)
- Water: 4 bar (catastrophic)

## **Sealing components**

#### **Sealing components**





Lubricant

RS sea

For detailed information, please visit roxtec.com.

2024-04-27





### **Pre-configured transit kits**

in/lbs







RS 31 AISI316



RS 43 AISI316



RS 50 AISI316



RS 68 AISI316



RS 75 AISI316



RS 100 AISI316



RS 125 AISI316



RS 100 AISI316 WOC



RS 125 AISI316 WOC



RS 150 AISI316 WOC



RS 175 AISI316 WOC



RS 200 AISI316 WOC



RS 225 AISI316 WOC



RS 250 AISI316 WOC



RS 300 AISI316 WOC





RS 350 AISI316 WOC RS 400 AISI316 WOC





RS 450 AISI316 WOC | RS 500 AISI316 WOC | RS 550 AISI316 WOC | RS 600 AISI316 WOC | RS 644 AISI316 WOC







Product	Configuration	Aperture dimensions ∅	Weight	Art. no
RS 25 AISI316	1x (0.142-0.472)	0.984 - 1.024	0.18	RS00100251023
RS 31 AISI316	1x (0.157-0.669)	1.22 - 1.26	0.2	RS00100311023
RS 43 AISI316	1x (0.157-0.906)	1.693 - 1.772	0.53	RS00100431023
RS 50 AISI316	1x (0.315-1.181)	1.969 - 2.047	0.68	RS00100501023
RS 68 AISI316	1x (1.024-1.890)	2.677 - 2.756	1.1	RS00100681023
RS 75 AISI316	1x (0.945-2.126)	2.953 - 3.031	1.4	RS00100751023
RS 100 AISI316	1x (1.890-2.756)	3.937 - 4.016	2.2	RS00101001023
RS 125 AISI316	1x (2.598-3.858)	4.921 - 5	3.5	RS00101251023
RS 100 AISI316 WOC	1x (1.890-2.756)	3.937 - 4.016	1.8	RS00001001023
RS 125 AISI316 WOC	1x (2.598-3.858)	4.921 - 5	3.1	RS00001251023
RS 150 AISI316 WOC	1x (3.661-4.685)	5.906 - 5.984	3.5	RS00001501023
RS 175 AISI316 WOC	1x (4.685-5.709)	6.89 - 6.969	5	RS00175750021
RS 200 AISI316 WOC	1x (5.433-6.693)	7.874 - 7.992	6	RS00200750021
RS 225 AISI316 WOC	1x (5.945-7.126)	8.858 - 8.976	7.1	RS00002250021
RS 250 AISI316 WOC	1x (6.929-8.110)	9.843 - 9.961	7.3	RS00002500021
RS 300 AISI316 WOC	1x (8.110-9.291)	11.811 - 11.929	12.6	RS00003000021
RS 350 AISI316 WOC	1x (9.606-11.260)	13.78 - 13.898	16	RS00003500021
RS 400 AISI316 WOC	1x (11.575-13.228)	15.748 - 15.866	20.7	RS00004000021
RS 450 AISI316 WOC	1x (13.543-15.197)	17.717 - 17.835	23.6	RS00004500021
RS 500 AISI316 WOC	1x (15.512-17.165)	19.685 - 19.803	28.5	RS00005000021
RS 550 AISI316 WOC	1x (17.480-19.134)	21.654 - 21.772	31.7	RS00005500021
RS 600 AISI316 WOC	1x (19.449-21.102)	23.622 - 23.74	34.6	RS00006000021
RS 644 AISI316 WOC	1x (21.181-22.835)	25.354 - 25.472	37.5	RS00006440021

2024-04-27 2/3



#### Read more about the solution on roxtec.com

https://www.roxtec.com/linktransit/en/solution/1113



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-27

3/3 2024-04-27