




Roxtec RS X 씰

용접이 허용되지 않거나 권장되지 않거 나 적합하지 않은 경우에 사용되는 관

Roxtec RS X는 슬리브를 갖춘 비용접형 씰로 단일 케이블 또는 파이프에 사용합니다. 관통 장비는 용접이 허용되지 않거나, 권장되지 않거나, 또는 적합하지 않은 경우의 유지 및 보수 시에 이상적입니다. 슬리브 바깥쪽에는 고무 개스킷이 있으며 볼트를 조이면 구멍 안에서 팽창하여 단단하게 안착시켜 줍니다. RS X 씰은 레이어를 제거할 수 있기 때문에 다양한 규격의 케이블 및 파이프에 적용할 수 있습니다.



이 유지/보수 용이

제품 특장점







설치 구조







기존구멍존

등급 및 인증

화재

IMO 2010 FTP 코드에 따른 A등급

강도

● 가스: 2.67 Bar(일시적인)

물: 4 Bar(일시적인)

씰링 컴포넌트 데이터

씰링 컴포넌트





RS X 키트

윤활제

자세한 내용은 roxtec.com을 방문하십시오.

2024-03-12







키트 구성의 관통장비

mm/kg







RS X 200 AISI316 WOC/GALV





RS X 100 AISI316/GALV RS X 43 AISI316/GALV RS X 125 AISI316/GALV





RS X 100 AISI316 WOC/GALV



RS X 175 AISI316 WOC/GALV



RS X 150 AISI316 WOC/GALV



RS X 125 AISI316 WOC/GALV



RS X 75 AISI316/GALV

구성	구성	홀 치수 Ø	무게	Art. 번호
RS X 50 AISI316/GALV	1x (8.0-30.0)	90 - 92	1.4	RSXG100501021
RS X 200 AISI316 WOC/GALV		250 - 252	6.6	RSXG002001021
RS X 100 AISI316/GALV	1x (48.0-70.0)	145 - 147	3.2	RSXG101001021
RS X 43 AISI316/GALV	1x (4.0-23.0)	82 - 84	0.8	RSXG100431021
RS X 125 AISI316/GALV	1x (66.0-98.0)	170 - 172	2.8	RSXG101251021
RS X 100 AISI316 WOC/GALV	1x (48.0-70.0)	145 - 147	3	RSXG001001021
RS X 175 AISI316 WOC/GALV		220 - 222	5	RSXG001751021
RS X 150 AISI316 WOC/GALV	1x (93.0-119.0)	199 - 201	5.2	RSXG001501021
RS X 125 AISI316 WOC/GALV	1x (66.0-98.0)	170 - 172	4	RSXG001251021
RS X 75 AISI316/GALV	1x (24.0-54.0)	115 - 117	2.2	RSXG100751021

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-03-12

2/2 2024-03-12