




Roxtec RS X 密封系统

这种穿隔系统适用于不允许、不建议或不希望焊接的情况。

Roxtec RS X 是一种带套筒的非焊接密封系统チ用于密封单根电缆或管道。其穿隔系统非常适合用于改造项目或不允许、不建议或不希望焊接的情况。当拧紧螺栓时チ套筒外侧的橡胶密封垫在开孔中膨胀チ实现牢固安装。RS X 密封系统配有可剥离芯层チ可灵活适配各种规格的电缆和管道。



完全适应改造









安装结构



安装类型



现有开孔

等级和证书

火灾

● A 级符合 IMO 2010 FTP 规范

密封性


气体: 2.67 barソ洪灾ゾ

/ (|本. 2.0/ Dui / /六)

水: 4 barソ洪灾ゾ

密封组件数据

密封组件





RS X 套件

润滑脂

如需了解详细信息チ请访问 roxtec.com。

2024-04-06





预装配的穿隔套件

mm/kg



RS X 100 AISI316 WOC/GALV



RS X 125 AISI316 WOC/GALV



RS X 150 AISI316 WOC/GALV



RS X 175 AISI316 WOC/GALV



RS X 200 AISI316 WOC/GALV





RS X 43 AISI316/GALV RS X 50 AISI316/GALV



RS X 75 AISI316/GALV





RS X 100 AISI316/GALV RS X 125 AISI316/GALV

标题	配置	开孔尺寸 ∅	重量	产品编号
RS X 100 AISI316 WOC/GALV	1x (48.0-70.0)	145 - 147	3	RSXG001001021
RS X 125 AISI316 WOC/GALV	1x (66.0-98.0)	170 - 172	4	RSXG001251021
RS X 150 AISI316 WOC/GALV	1x (93.0-119.0)	199 - 201	5.2	RSXG001501021
RS X 175 AISI316 WOC/GALV		220 - 222	5	RSXG001751021
RS X 200 AISI316 WOC/GALV		250 - 252	6.6	RSXG002001021
RS X 43 AISI316/GALV	1x (4.0-23.0)	82 - 84	0.8	RSXG100431021
RS X 50 AISI316/GALV	1x (8.0-30.0)	90 - 92	1.4	RSXG100501021
RS X 75 AISI316/GALV	1x (24.0-54.0)	115 - 117	2.2	RSXG100751021
RS X 100 AISI316/GALV	1x (48.0-70.0)	145 - 147	3.2	RSXG101001021
RS X 125 AISI316/GALV	1x (66.0-98.0)	170 - 172	2.8	RSXG101251021

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-06

2/2 2024-04-06