




Roxtec RS PPS/S シール

一方の側だけで完了する施工用の、軽量のプ

Roxtec RS PPS/S

は、鋼製のデッキと隔壁などの防火区域のプラスチックパイプ付き開口部用のシールです 。シールは、火災が発生した場合に煙、炎、水を完全にブロックし、一方の側だけで完了 する施工の認可を取得しています。剥がせるレイヤーによって、貫通部は異なる外径のパ イプに対応可能です。最長119 mmのプラスチックパイプ向けです。





- 迅速で簡単な施工
- 異なる外径のケーブル・パイプに対応可能

製品特性







設置構造



取り付けタイプ



規格と認証証明書

火災

- A級 IMO 2010 FTP コードに基づく試験
- E/EI 等級 EN 45545に基づく試験

密性

- ガス: 2 バール (衝撃圧)
- 水: 4 バール (衝撃圧)

シーリングコンポーネントのデータ

シーリングコンポーネント





RS PPS/Sシー

潤滑剤

詳細情報については、roxtec.com をご覧ください。

2024-03-20

https://www.roxtec.com/linktransit/ja-jp/solution/1121







設定済み貫通部キット

mm/kg

















RS PPS/S 31 AISI316

RS PPS/S 43 AISI316

RS PPS/S 50 AISI316

RS PPS/S 68 AISI316

RS PPS/S 75 AISI316

RS PPS/S 100 AISI316 WOC

RS PPS/S 125 AISI316 WOC

RS PPS/S 150 AISI316 WOC

| タイトル | 構成 | 開口部寸法 ∅ | 重量部品番号 | |
|--------------------------|-----------------|------------|-------------------|-----|
| RS PPS/S 31 AISI316 | 1x (4.0-17.0) | 31 - 32 | 0.09 PPSS0000031: | 21 |
| RS PPS/S 43 AISI316 | 1x (4.0-23.0) | 43 - 45 | 0.29 PPSS0000043 | 321 |
| RS PPS/S 50 AISI316 | 1x (8.0-30.0) | 50 - 52 | 0.37 PPSS0000050 |)21 |
| RS PPS/S 68 AISI316 | 1x (26.0-48.0) | 68 - 70 | 0.6 PPSS0000068 | 321 |
| RS PPS/S 75 AISI316 | 1x (24.0-54.0) | 75 - 77 | 0.6 PPSS0000075 | 21 |
| RS PPS/S 100 AISI316 WOC | 1x (48.0-70.0) | 100 - 102 | 0.8 PPSS0000100 | 21 |
| RS PPS/S 125 AISI316 WOC | 1x (66.0-98.0) | 125 - 127 | 1.4 PPSS00001252 | 21 |
| RS PPS/S 150 AISI316 WOC | 1x (93.0-119.0) | 150 - 152 | 1.6 PPSS0000150 | 21 |

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from

https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/
We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-03-20

2/2 2024-03-20