




带有 SL RS 的 Roxtec RS PPS/S 密封系统

用干单侧安装的轻型塑料管道密封系统。

带有 SL RS 的 Roxtec RS PPS/S 密封系统可用于钢制甲板和舱壁等耐火区域带塑料管道的 开孔。其密封系统可在发生火灾时确保完全阻断烟雾、火焰和水チ并已获得单侧安装认证 。其穿隔系统具备可剥离芯层チ可灵活适配各种规格的管道チ并配有可焊接在结构 上的套筒。用于直径 119 毫米以内的塑料管道。



安装快速便捷



产品特性







安装类型





安装结构

等级和证书

火灾

A 级符合 IMO 2010 FTP 规范



E/EI 等级符合 EN 45545 E60

密封性

气体: 2 barソ洪灾ゾ

水: 4 barソ洪灾ゾ

密封组件数据

密封组件







润滑脂

SL RS 套筒

RS PPS/S 密封件

如需了解详细信息チ请访问 roxtec.com。

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or

common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from

https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/
We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-07-05



Roxtec @ and Multidiameter @ are registered trademarks of Roxtec in Sweden and/or other countries.