



Roxtec S transit with SE PPS

Transit for multiple plastic pipes.

The Roxtec SE PPS with S is an extension of a standard Roxtec transit for protection of multiple plastic pipe penetrations against the risk of fire. The seal allows for a mix of pipe materials (metal and plastic) and in some cases cables within the same opening. The S frame is for welding to the structure. The standard sealing modules are adaptable to cables and pipes of different sizes, and can be used to build in spare capacity in the transit.

Area efficient



Product characteristics





Structure of installation





Mounting type

Ratings & certificates

Fire

A-CLASS according to IMO 2010 FTP Code

Tightness

- Gas: 2.5 bar (catastrophic)
- Water: 4 bar (catastrophic)

Frame dimensions

mm/kg

The frame variants below are a limited selection. For the full range of frames and configurations, please visit roxtec.com.

Product	Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
S 6x1 ALU	1	120 x 180	140.5 x 238 x 60	143(+1/-1) × 240(+1/-1)	1.2	S00600000131
S 6x1 PRIMED	1	120 x 180	140.5 x 238 x 60	143(+1/-1) x 240(+1/-1)	3.3	S00600000112
S 6x1 AISI316	1	120 x 180	140.5 x 238 x 60	143(+1/-1) × 240(+1/-1)	3.3	S00600000121
S 6x2 ALU	2	120 x 180	271 x 238 x 60	273(+1/-1) x 240(+1/-1)	1.9	S00600000231
S 6x2 AISI316	2	120 x 180	271 x 238 x 60	273(+1/-1) × 240(+1/-1)	5.5	S00600000221
S 6x2 PRIMED	2	120 x 180	271 x 238 x 60	273(+1/-1) x 240(+1/-1)	5.5	S00600000212
S 6x3 PRIMED	3	120 x 180	401.5 x 238 x 60	404(+1/-1) × 240(+1/-1)	7.7	S00600000312
S 6x3 AISI316	3	120 x 180	401.5 x 238 x 60	404(+1/-1) × 240(+1/-1)	7.7	S00600000321
S 6x3 ALU	3	120 x 180	401.5 x 238 x 60	404(+1/-1) x 240(+1/-1)	2.6	\$00600000331



Accessories



Holder tools

Sealing components

Sealing components



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect,

consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/ We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtee International AB and is protected by copyright. This document was generated on: 2024-04-27