



# SE PPS 付き Roxtec S 貫通部フレーム

複数のプラスチックパイプ用の貫通部です。

Roxtec S付きのRoxtec SE PPS

は、火災の危険性に対する複数のプラスチックパイプの貫通の保護のための、標準的なRoxtecの貫通部の拡張です。シールは、パイプの素材(金属とプラスチック)と、場合によってはケーブルを、同じ開口部内に混在させることが可能です。Sフレームは構造への溶接用です。標準的なシーリングモジュールは異なる外径のケーブルやパイプに対応可能で、貫通部に将来の予備スペースを確保するために使用できます。

- 優れた面積効率



## 製品特性



耐火



防水



気密

## 設置構造



金属

## 取り付けタイプ



溶接

## 規格と認証証明書

### 火災

- A 級 IMO 2010 FTP コードに基づく試験

### 密性

- ガス: 2.5 バール (衝撃圧)
- 水: 4 バール (衝撃圧)

## フレーム寸法

mm/kg

以下のフレームは一部です。フレームと構成品の全ラインナップについては、[roxtec.com](https://www.roxtec.com) をご覧ください。

タイトル	フレームの開口部	バックスペース	外径 WxD	開口部寸法 w x h	重量	部品番号
S 6x1 ALU	1	120 x 180	140.5 x 238 x 60	143(+1/-1) x 240(+1/-1)	1.2	S006000000131
S 6x1 PRIMED	1	120 x 180	140.5 x 238 x 60	143(+1/-1) x 240(+1/-1)	3.3	S006000000112
S 6x1 AISI316	1	120 x 180	140.5 x 238 x 60	143(+1/-1) x 240(+1/-1)	3.3	S006000000121
S 6x2 PRIMED	2	120 x 180	271 x 238 x 60	273(+1/-1) x 240(+1/-1)	5.5	S006000000212
S 6x2 ALU	2	120 x 180	271 x 238 x 60	273(+1/-1) x 240(+1/-1)	1.9	S006000000231
S 6x2 AISI316	2	120 x 180	271 x 238 x 60	273(+1/-1) x 240(+1/-1)	5.5	S006000000221
S 6x3 PRIMED	3	120 x 180	401.5 x 238 x 60	404(+1/-1) x 240(+1/-1)	7.7	S006000000312
S 6x3 AISI316	3	120 x 180	401.5 x 238 x 60	404(+1/-1) x 240(+1/-1)	7.7	S006000000321
S 6x3 ALU	3	120 x 180	401.5 x 238 x 60	404(+1/-1) x 240(+1/-1)	2.6	S006000000331



# シーリングコンポーネントのデータ


## シーリングコンポーネント




潤滑剤




ウェッジおよびウェット



Multidiameter™ 付き RM



RM ソリッドコン  
ンセンション モジュ



ステイプレート



SE PPS 拡張フ



ホルダー・ツール



シーリングキット



溶接用ツール

詳細情報については、[roxtec.com](https://www.roxtec.com) をご覧ください。

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-11