




配有 SE PPS 的 Roxtec SF 穿隔系统

用于多根塑料管道的穿隔系统。

Roxtec SE PPS with SF 是标准 Roxtec 穿隔系统的扩展型号チ用于保护 多根塑料管道穿隔系统免受火灾侵害。其密封系统

可用于混合管道材料ソ金属和塑料ゾチ并在一些情况下チ可用于相同开孔内的电缆

。其穿隔框架配有一个法兰チ可简化焊接到不精确开孔的过程。这种标准密封模块可灵活适 配各种规格的电缆和管道チ并可在穿隔系统内提供备用容量。















安装结构



安装类型



等级和证书

火灾

● A 级符合 IMO 2010 FTP 规范

密封性


气体: 2.5 barソ洪灾ゾ

水: 4 barソ洪灾ゾ

框架尺寸

mm/kg

下方的不同框架只是部分选择。 要了解全部的框架和配置チ请访问 roxtec.com。



1-8±	45 to True	rtn+4-rtn277		#7 D-4	.	÷ 0.460
_ 标题	框架开口	密封空间	外部尺寸 WxHxD	开孔尺寸 w x h	重量	产品编号
SF 6x1 ALU	1	120 x 180	260.5 x 358 x 60	201(+15/-15) x 298(+15/-15)	2.9	SFF6000000131
SF 6x2 ALU	2	120 x 180	391 x 358 x 60	332(+15/-15) x 298(+15/-15)	4.2	SFF6000000231
SF 6x3 ALU	3	120 x 180	521.5 x 358 x 60	462(+15/-15) x 298(+15/-15)	6	SFF6000000331
SF 6x1 PRIMED	1	120 x 180	260.5 x 358 x 60	201(+15/-15) x 298(+15/-15)	7.6	SFF6000000112
SF 6x2 PRIMED	2	120 x 180	391 x 358 x 60	332(+15/-15) x 298(+15/-15)	12	SFF6000000212
SF 6x3 PRIMED	3	120 x 180	521.5 x 358 x 60	462(+15/-15) x 298(+15/-15)	16.4	SFF6000000312
SF 6x1 AISI316	1	120 x 180	260.5 x 358 x 60	201(+15/-15) x 298(+15/-15)	8.2	SFF6000000121
SF 6x2 AISI316	2	120 x 180	391 x 358 x 60	332(+15/-15) x 298(+15/-15)	12.2	SFF6000000221
SF 6x3 AISI316	3	120 x 180	521.5 x 358 x 60	462(+15/-15) x 298(+15/-15)	16.6	SFF6000000321

1/2 2025-07-03



https://www.roxtec.com/linktransit/zh-cn/solution/1131

配件



密封组件数据

密封组件







RM 盲堵模块



密封套件





隔层板



润滑脂



SE PPS 扩展型框架



焊接工具



支架工具

楔形压紧件和楔形压紧套件

如需了解详细信息チ请访问 roxtec.com。

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-07-03



Roxtec ® and Multidiameter ® are registered trademarks of Roxtec in Sweden and/or other countries.

2025-07-03