



Roxtec SF welded Ex transit

Transit with metal frame for welding to enclosures.

The Roxtec SF W Ex is a high cable density transit rated for Ex e and Ex tb areas in temperatures from -60 to +80° C. The seal is for use with cables larger than 34,5mm in diameter. The transit frame has a flange to simplify welding to unprecise holes and is produced in 10mm thick metal.

Provides built-in spare capacity





IΡ

IP/UL NEMA





Structure of installation

Fire rated

Metal



Welding



Ratings & certificates

Fire

- A-CLASS according to IMO 2010 FTP Code
- H-CLASS according to IMO 2010 FTP Code + HC fire load curve

Tightness

IP 66/67

Supports

- Bonding and grounding
- Electromagnetic shielding
- Potential equalization
- Ex rated

Frame dimensions

in/lbs

The frame variants below are a limited selection. For the full range of frames and configurations, please visit roxtec.com.

	<u>، </u>	Product	Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
	H	SF 6x1 W Ex PRIMED	1	4.724 x 7.087	10.256 x 14.094 x 2.362	7.894(+1.181/-1.181) x 11.732(+1.181/-1.181)	18.1	EXSF00600000112
		SF 6x2 W Ex PRIMED	2	4.724 x 7.087	15.394 x 14.094 x 2.362	13.031(+1.181/-1.181) x 11.732(+1.181/-1.181)	26	EXSF00600000212
		SF 6x3 W Ex PRIMED	3	4.724 x 7.087	20.531 x 14.094 x 2.362	18.169(+1.181/-1.181) x 11.732(+1.181/-1.181)	33.7	EXSF0060000312
		SF 6x1 W Ex AISI316	1	4.724 x 7.087	10.256 x 14.094 x 2.362	7.894(+1.181/-1.181) x 11.732(+1.181/-1.181)	17.9	EXSF00600000121
w.		SF 6x2 W Ex AISI316	2	4.724 x 7.087	15.394 x 14.094 x 2.362	13.031(+1.181/-1.181) x 11.732(+1.181/-1.181)	26	EXSF0060000221
		SF 6x3 W Ex AISI316	3	4.724 x 7.087	20.531 x 14.094 x 2.362	18.169(+1.181/-1.181) x 11.732(+1.181/-1.181)	33.7	EXSF0060000321





Sealing components

Sealing components



Lubricant



Wedge & Wedgekit Ex



RM Ex solid compensation module



RM Ex module with

Multidiameter™





Accessories



Wedge & Wedgekit ES Ex

Holder tools

Welding tools





RM ES Ex module with compensation module Multidiameter



RM ES Ex solid compensation module



RM PE Ex module with Multidiameter

RM BG[™] Ex module with Multidiameter





RM BG™ Ex solid

RM PE Ex solid compensation module

Ex sealing kit

For detailed information, please visit roxtec.com.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect,

Consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/ We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-27