



Roxtec SFHM 穿隔系统

这种穿隔系统配有金属框架和法兰チ可栓接到结构上。

Roxtec SFHMソ含密封垫ゾ电缆和管道穿隔系统可提供采用不同材料制成的型号チ用于 单开孔或多种组合开孔。其穿隔框架配有法兰チ采用 10 毫米厚的金属制成チ带有 TSL 密封条チ可栓接到结构上。这种标准密封模块可灵活适配各种规格的电缆 和管道チ并可在穿隔系统内提供备用容量。







易于维护和检查

产品特性











安装类型

等级和证书

火灾 ● A 级符合 IMO 2010 FTP 规范

● H级符合 IMO 2010 FTP 规范 + HC 火灾荷载曲线

喷射火符合 ISO 22899-1 和 OTI 95634 标准

密封性




水: 4 barソ洪灾ゾ

框架尺寸

mm/kg

下方的不同框架只是部分选择。 要了解全部的框架和配置チ请访问 roxtec.com。



| + | _ 标题 - | 框架开口 | 密封空间 | 外部尺寸 WxHxD | 开孔尺寸 w×h | 重量 | 产品编号 |
|---|-----------------------------------|------|-----------|----------------------|-------------|------|---------------|
| | SFHM 6x1 ALU INCL TSL 15x6 | 1 | 120 x 180 | 260.5 x 358 x 60 | | 2.8 | 5SFHM00008469 |
| 1 | SFHM 6x2 ALU INCL TSL 15x6 | 2 | 120 x 180 | 391 x 358 x 60 | | 2.8 | 5SFHM00008461 |
| | SFHM 6x3 ALU INCL TSL 15x6 | 3 | 120 x 180 | 521.5 x 358 x 60 | | 5.4 | 154739 |
| | SFHM 6x1 PRIMED INCL TSL 15x6 | 1 | 120 x 180 | 260.5 x 358 x 60 | | 8.1 | 5SFHM00009087 |
| | SFHM 6x2 PRIMED INCL TSL 15x6 | 2 | 120 x 180 | 391 x 358 x 60 | | 11.8 | 120964 |
| | SFHM 6x3 PRIMED INCL TSL 15x6 | 3 | 120 x 180 | 521.5 x 358 x 60 | | 15.3 | 123095 |
| | SFHM 6x1 AISI316 INCL TSL 15x6 | 1 | 120 x 180 | 260.5 x 358 x 60 | | 8 | 5SFHM00007863 |
| | SFHM 6x2 AISI316 INCL TSL 15x6 | 2 | 120 x 180 | 391 x 358 x 60 | | 11.5 | 5SFHM00009102 |
| | SFHM 6x3 AISI316 INCL TSL 15x6 | 3 | 120 x 180 | 521.5 x 358 x 60 | | 14.9 | 5SFHM00007864 |

2024-04-09







Roxtec

密封组件数据

密封组件













润滑脂

楔形压紧件和楔形压紧套件 Multidiameter™ソ多径ゾ

RM 模块

RM 盲堵模块

隔层板

支架工具



密封套件

如需了解详细信息チ请访问 roxtec.com。

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect,

consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from

THE NOXIEC products are othered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/
We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.
This document was generated on: 2024-04-09

2/2 2024-04-09