




Roxtec Sleeve-it™ Fire penetration seal

Fire penetration seal for single plastic pipes.

The Roxtec Sleeve-it™ Fire penetration seal is a light-weight and versatile solution. Its stainless steel casing contains intumescent material which closes off the penetration in case of fire. It is installed from one side and is openable so it can be used for both new-build and retrofit. It is available for both steel and aluminum structures.



- Light-weight
- Area efficient
- Quick and easy to install

Product characteristics



Fire rated

Structure of installation



Metal

Mounting type



Welding

Ratings & certificates

Fire

- A-CLASS according to IMO 2010 FTP Code
- B-CLASS according to IMO 2010 FTP Code

Sealing components

Sealing components



Sleeve-it™ Fire penetration seal

Accessories














fire sealant

For detailed information, please visit [roxtec.com](https://www.roxtec.com).



Pre-configured transit kits

mm/kg

							
SLEEVE-IT FC-MAR16M	SLEEVE-IT FC-MAR20M	SLEEVE-IT FC-MAR25M	SLEEVE-IT FC-MAR32M	SLEEVE-IT FC-MAR40M	SLEEVE-IT FC-MAR50M (1.5")	SLEEVE-IT FC-MAR60M (2")	SLEEVE-IT FC-MAR63M
							
SLEEVE-IT FC-MAR66M	SLEEVE-IT FC-MAR75M	SLEEVE-IT FC-MAR82M	SLEEVE-IT FC-MAR90M (3")	SLEEVE-IT FC-MAR110M	SLEEVE-IT FC-MAR115M (4")	SLEEVE-IT FC-MAR125M	SLEEVE-IT FC-MAR140M
							
SLEEVE-IT FC-MAR160M	SLEEVE-IT FC-MAR169M (6")	SLEEVE-IT FC-MAR200M	SLEEVE-IT FC-MAR219M (8")	SLEEVE-IT FC-MAR225M	SLEEVE-IT FC MAR16M ALU	SLEEVE-IT FC MAR20M ALU	SLEEVE-IT FC MAR25M ALU
							
SLEEVE-IT FC MAR32M ALU	SLEEVE-IT FC MAR40M ALU	SLEEVE-IT FC MAR50M ALU (1.5")	SLEEVE-IT FC MAR60M ALU (2")	SLEEVE-IT FC MAR63M ALU	SLEEVE-IT FC MAR66M ALU	SLEEVE-IT FC MAR75M ALU	SLEEVE-IT FC MAR82M ALU
							
SLEEVE-IT FC MAR90M ALU (3")	SLEEVE-IT FC MAR110M ALU	SLEEVE-IT FC MAR115M ALU (4")	SLEEVE-IT FC MAR125M ALU	SLEEVE-IT FC MAR140M ALU	SLEEVE-IT FC MAR160M ALU	SLEEVE-IT FC MAR169M ALU (6")	SLEEVE-IT FC MAR200M ALU
							
SLEEVE-IT FC MAR219M ALU (8")	SLEEVE-IT FC MAR225M ALU						



Product	Configuration	Aperture dimensions Ø	Weight	Art. no
SLEEV-IT FC-MAR16M		18 - 26	0.11	106239
SLEEV-IT FC-MAR20M		22 - 30	0.13	106245
SLEEV-IT FC-MAR25M		27 - 35	0.14	106247
SLEEV-IT FC-MAR32M		34 - 42	0.17	106249
SLEEV-IT FC-MAR40M		42 - 50	0.21	106251
SLEEV-IT FC-MAR50M (1.5")		50 - 58	0.36	106253
SLEEV-IT FC-MAR60M (2")		62 - 70	0.4	106255
SLEEV-IT FC-MAR63M		65 - 73	0.41	106257
SLEEV-IT FC-MAR66M		68 - 76	0.5	117916
SLEEV-IT FC-MAR75M		77 - 85	0.6	106259
SLEEV-IT FC-MAR82M		84 - 92	0.6	117919
SLEEV-IT FC-MAR90M (3")		91 - 99	0.7	106261
SLEEV-IT FC-MAR110M		112 - 120	0.8	106263
SLEEV-IT FC-MAR115M (4")		116 - 124	0.8	106265
SLEEV-IT FC-MAR125M		127 - 135	0.9	106267
SLEEV-IT FC-MAR140M		142 - 150	1	106269
SLEEV-IT FC-MAR160M		162 - 170	1.3	106271
SLEEV-IT FC-MAR169M (6")		170 - 178	1.4	106273
SLEEV-IT FC-MAR200M		202 - 210	1.9	106275
SLEEV-IT FC-MAR219M (8")		221 - 229	2	106278
SLEEV-IT FC-MAR225M		227 - 235	2.1	106280
SLEEV-IT FC MAR16M ALU		20 - 26	0.2	151280
SLEEV-IT FC MAR20M ALU		24 - 30	0.16	151281
SLEEV-IT FC MAR25M ALU		29 - 35	0.17	151282
SLEEV-IT FC MAR32M ALU		36 - 42	0.2	151283
SLEEV-IT FC MAR40M ALU		44 - 50	0.22	151284
SLEEV-IT FC MAR50M ALU (1.5")		52 - 58	0.3	151285
SLEEV-IT FC MAR60M ALU (2")		64 - 70	0.3	151286
SLEEV-IT FC MAR63M ALU		67 - 73	0.4	151287
SLEEV-IT FC MAR66M ALU		68 - 76	0.4	153747
SLEEV-IT FC MAR75M ALU		79 - 85	0.4	151288
SLEEV-IT FC MAR82M ALU		86 - 92	0.5	153748
SLEEV-IT FC MAR90M ALU (3")		93 - 99	0.5	151289
SLEEV-IT FC MAR110M ALU		112 - 120	0.7	151290
SLEEV-IT FC MAR115M ALU (4")		118 - 124	0.7	151291
SLEEV-IT FC MAR125M ALU		129 - 135	0.8	151292
SLEEV-IT FC MAR140M ALU		144 - 150	1	151293
SLEEV-IT FC MAR160M ALU		164 - 170	1	151294
SLEEV-IT FC MAR169M ALU (6")		172 - 178	1.1	151295
SLEEV-IT FC MAR200M ALU		204 - 210	1.5	151296
SLEEV-IT FC MAR219M ALU (8")		223 - 229	1.6	151297
SLEEV-IT FC MAR225M ALU		229 - 235	1.7	151298

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/> We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-11