




# **Roxtec Sleev-it™ Waterproof penetration** sea

Penetration seal for plastic pipes for basic protection against fire, gas and water.

The Roxtec Sleev-it™ Waterproof penetration seal is a light-weight solution. Its stainless steel casing contains intumescent material to block the penetration in case of fire and its rubber grommet is engineered for a range of pipe sizes. It is installed from one side and is available for both steel and aluminum structures.



#### Light-weight

### Area efficient

Quick and easy to install

#### **Product characteristics**





Fire rated

Structure of installation



Mounting type



**Ratings & certificates** 

A-CLASS according to IMO 2010 FTP Code

B-CLASS according to IMO 2010 FTP Code

#### **Tightness**

Water: 1 bar (catastrophic)

## **Sealing components**

#### **Sealing components**



Sleev-it™ Waterproof penetration seal

For detailed information, please visit roxtec.com.

2024-04-15





## **Pre-configured transit kits**

in/lbs

















SLEEV-IT WT-MAR16M SLEEV-IT WT-MAR20M SLEEV-IT WT-MAR25M SLEEV-IT WT-MAR32M SLEEV-IT WT-MAR40M SLEEV-IT WT-MAR50M SLEEV-IT WT-MAR50M SLEEV-IT WT-MAR50M

















SLEEV-IT WT-MAR63M SLEEV-IT WT-MAR75M SLEEV-IT WT-MAR90M SLEEV-IT WT-MAR90M SLEEV-IT WT-MAR110M SLEEV-IT WT-MAR115M SLEEV-IT WT-MAR125M





SLEEV-IT WT-MAR169M (6")



SLEEV-IT WT-MAR200M





ALU



SLEEV-IT WT MAR16M SLEEV-IT WT MAR20M SLEEV-IT WT MAR25M SLEEV-IT WT MAR32M ALU ALU ALU ALU

ALU (6")











ALU (2")









SLEEV-IT WT MAR40M SLEEV-IT WT MAR50M SLEEV-IT WT MAR50M SLEEV-IT WT MAR60M SLEEV-IT WT MAR63M SLEEV-IT WT MAR75M SLEEV-IT WT MAR90M SLEEV-IT WT M







ALU (4")







SLEEV-IT WT MAR200M ALU

2/3 2024-04-15



#### https://www.roxtec.com/linktransit/en-us/solution/1138



Product	Configuration	Aperture dimensions ∅	Weight	Art. no
SLEEV-IT WT-MAR16M		1.417 - 1.811	0.55	106315
SLEEV-IT WT-MAR20M		1.732 - 2.126	0.71	106316
SLEEV-IT WT-MAR25M		1.811 - 2.205	0.75	106319
SLEEV-IT WT-MAR32M		2.087 - 2.48	0.84	106322
SLEEV-IT WT-MAR40M		2.52 - 2.913	0.9	106325
SLEEV-IT WT-MAR50M (1.5")		2.913 - 3.307	1.1	106359
SLEEV-IT WT-MAR50M		2.913 - 3.307	1.1	106328
SLEEV-IT WT-MAR60M (2")		3.346 - 3.74	1.1	106362
SLEEV-IT WT-MAR63M		3.465 - 3.858	1.2	106331
SLEEV-IT WT-MAR75M		4.213 - 4.606	1.7	106334
SLEEV-IT WT-MAR90M (3")		5.079 - 5.472	2.2	106365
SLEEV-IT WT-MAR90M		5 - 5.394	2.1	106337
SLEEV-IT WT-MAR110M		5.827 - 6.22	2.6	106341
SLEEV-IT WT-MAR115M (4")		5.787 - 6.181	2.6	106371
SLEEV-IT WT-MAR125M		6.575 - 6.969	3	106344
SLEEV-IT WT-MAR140M		6.89 - 7.283	3.5	106347
SLEEV-IT WT-MAR160M		8.268 - 8.661	4	106350
SLEEV-IT WT-MAR169M (6")		8.661 - 9.055	4.5	106373
SLEEV-IT WT-MAR200M		9.646 - 10.039	6.6	106353
SLEEV-IT WT-MAR225M		11.22 - 11.614	8.3	106356
SLEEV-IT WT MAR16M ALU		1.85 - 2.087	0.33	151259
SLEEV-IT WT MAR20M ALU		2.087 - 2.323	0.4	151260
SLEEV-IT WT MAR25M ALU		2.323 - 2.559	0.44	151261
SLEEV-IT WT MAR32M ALU		2.598 - 2.835	0.66	151262
SLEEV-IT WT MAR40M ALU		2.874 - 3.11	0.66	151263
SLEEV-IT WT MAR50M ALU (1.5")		3.189 - 3.425	0.66	151264
SLEEV-IT WT MAR50M ALU		3.268 - 3.504	0.66	151265
SLEEV-IT WT MAR60M ALU (2")		3.819 - 4.055	0.88	151266
SLEEV-IT WT MAR63M ALU		3.937 - 4.173	0.88	151267
SLEEV-IT WT MAR75M ALU		4.606 - 4.843	1.1	151268
SLEEV-IT WT MAR90M ALU (3")		5.157 - 5.394	1.5	151269
SLEEV-IT WT MAR90M ALU		5.197 - 5.433	1.5	151270
SLEEV-IT WT MAR110M ALU		6.181 - 6.417	1.8	151271
SLEEV-IT WT MAR115M ALU (4")		6.417 - 6.654	2	151272
SLEEV-IT WT MAR125M ALU		6.772 - 7.008	2.2	151273
SLEEV-IT WT MAR140M ALU		7.559 - 7.795	2.4	151274
SLEEV-IT WT MAR160M ALU		8.346 - 8.583	2.4	151275
SLEEV-IT WT MAR169M ALU (6")		8.701 - 8.937	3.1	151276
SLEEV-IT WT MAR200M ALU		10.315 - 10.551	4	151277

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-15

3/3 2024-04-15