



Roxtec SPM™ seal

Seal for metal pipes for use when welding is not allowed, recommended or desired.

The Roxtec SPM™ seal is a light-weight non-weld solution for single metal pipe entries. The transit is flexible towards pipe sizes as well as to uneven openings. The pipe seal is installed directly into structures without welding and has indicators showing when full compression is achieved.



- Light-weight
- Quick and easy to install
- Easy to maintain and inspect

Product characteristics



Fire rated



Watertight



Gas-tight

Structure of installation



Metal

Mounting type



Existing hole

Ratings & certificates

Fire


- A-CLASS according to IMO 2010 FTP Code

Tightness

- Gas: 0.67 bar (catastrophic)
- Water: 1 bar (catastrophic)

Sealing components

Sealing components



SPM™ seal




Lubricant

For detailed information, please visit [roxtec.com](https://www.roxtec.com).




Pre-configured transit kits


mm/kg




SPM 39




SPM 41




SPM 48




SPM 54




SPM 59




SPM 62




SPM 69




SPM 77




SPM 81




SPM 87




SPM 92




SPM 103




SPM 119




SPM 138




SPM 149




SPM 157




SPM 168




SPM 178




SPM 188




SPM 196




SPM 217




SPM 226




SPM 279




SPM 110



SPM 125



SPM 153



SPM 266



| Product | Configuration | Aperture dimensions Ø | Weight | Art. no |
|---------|------------------|--------------------------|--------|---------|
| SPM 39 | 1x (8.0-12.0) | 39 - 43 | 0.14 | 167591 |
| SPM 41 | 1x (12.0-16.0) | 41 - 45 | 0.14 | 153052 |
| SPM 48 | 1x (16.0-20.0) | 48 - 52 | 0.2 | 167592 |
| SPM 54 | 1x (19.0-23.0) | 53.5 - 57.5 | 0.25 | 153060 |
| SPM 59 | 1x (24.0-28.0) | 58.5 - 62.5 | 0.3 | 153064 |
| SPM 62 | 1x (27.0-31.0) | 61.5 - 65.5 | 0.32 | 153068 |
| SPM 69 | 1x (32.0-36.0) | 68.5 - 72.5 | 0.37 | 153072 |
| SPM 77 | 1x (37.0-42.0) | 77 - 81 | 0.47 | 166011 |
| SPM 81 | 1x (41.4-45.4) | 81 - 85 | 0.45 | 153040 |
| SPM 87 | 1x (47.0-51.0) | 87 - 91 | 0.5 | 153076 |
| SPM 92 | 1x (52.0-56.0) | 92 - 96 | 0.5 | 153080 |
| SPM 103 | 1x (56.2-61.1) | 103 - 107 | 0.7 | 153084 |
| SPM 119 | 1x (72.2-76.9) | 119 - 123 | 0.8 | 153088 |
| SPM 138 | 1x (88.0-92.0) | 138 - 142 | 1.2 | 153056 |
| SPM 149 | 1x (99.0-103.0) | 149 - 153 | 1.2 | 167594 |
| SPM 157 | 1x (107.0-111.0) | 157 - 161 | 1.2 | 153092 |
| SPM 168 | 1x (113.0-117.0) | 168 - 172 | 1.6 | 153096 |
| SPM 178 | 1x (123.0-127.0) | 178 - 182 | 1.7 | 167595 |
| SPM 188 | 1x (131.0-135.0) | 188 - 192 | 1.9 | 167596 |
| SPM 196 | 1x (138.5-143.0) | 196 - 200 | 1.9 | 153100 |
| SPM 217 | 1x (157.0-162.0) | 217 - 221 | 2.3 | 167597 |
| SPM 226 | 1x (167.0-171.0) | 226 - 230 | 2.4 | 153104 |
| SPM 279 | 1x (218.0-222.0) | 279 - 283 | 3.3 | 153036 |
| SPM 110 | 1x (65.0-69.0) | 110 - 114 | 0.7 | 206104 |
| SPM 125 | 1x (77.0-81.0) | 125 - 129 | 0.9 | 206108 |
| SPM 153 | 1x (103.0-107.0) | 153 - 157 | 1.2 | 206112 |
| SPM 266 | 1x (206.0-210.0) | 266 - 270 | 2.9 | 206124 |

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>. We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-05