



## Roxtec SPM<sup>™</sup> sea

Seal for metal pipes for use when welding is not allowed, recommended or desired.

The Roxtec SPM<sup>™</sup> seal is a light-weight non-weld solution for single metal pipe entries. The transit is flexible towards pipe sizes as well as to uneven openings. The pipe seal is installed directly into structures without welding and has indicators showing when full compression is achieved.



- Light-weight Quick and easy to install
- Easy to maintain and inspect

#### **Product characteristics**

Structure of installation

Fire rated



Watertight

Mounting type

Existing hole



## **Ratings & certificates**

Fire

A-CLASS according to IMO 2010 FTP Code

#### Tightness

- Gas: 0.67 bar (catastrophic)
- Water: 1 bar (catastrophic)

### **Sealing components**

#### Sealing components



For detailed information, please visit roxtec.com.





# Pre-configured transit kits

SPM 39	SPM 41	SPM 48	SPM 54	SPM 59	SPM 62	SPM 69	SPM 77
SPM 81	SPM 87	SPM 92	SPM 103	SPM 110	SPM 119	SPM 125	SPM 138
SPM 149	SPM 153	SPM 157	SPM 168	SPM 178	SPM 188	SPM 196	SPM 217
SPM 226	SPM 266	SPM 279					



https://www.roxtec.com/linktransit/en/solution/1139



Product	Configuration	Aperture dimensions Ø	Weight	Art. no
SPM 39	1x (0.315-0.472)	1.535 - 1.693	0.31	167591
SPM 41	1x (0.472-0.630)	1.614 - 1.772	0.31	153052
SPM 48	1x (0.630-0.787)	1.89 - 2.047	0.44	167592
SPM 54	1x (0.748-0.906)	2.106 - 2.264	0.55	153060
SPM 59	1x (0.945-1.102)	2.303 - 2.461	0.66	153064
SPM 62	1x (1.063-1.220)	2.421 - 2.579	0.71	153068
SPM 69	1x (1.260-1.417)	2.697 - 2.854	0.82	153072
SPM 77	1x (1.457-1.654)	3.031 - 3.189	1	166011
SPM 81	1x (1.630-1.787)	3.189 - 3.346	0.99	153040
SPM 87	1x (1.850-2.008)	3.425 - 3.583	1.1	153076
SPM 92	1x (2.047-2.205)	3.622 - 3.78	1.2	153080
SPM 103	1x (2.213-2.406)	4.055 - 4.213	1.5	153084
SPM 110	1x (2.559-2.717)	4.331 - 4.488	1.5	206104
SPM 119	1x (2.843-3.028)	4.685 - 4.843	1.8	153088
SPM 125	1x (3.031-3.189)	4.921 - 5.079	2	206108
SPM 138	1x (3.465-3.622)	5.433 - 5.591	2.5	153056
SPM 149	1x (3.898-4.055)	5.866 - 6.024	2.6	167594
SPM 153	1x (4.055-4.213)	6.024 - 6.181	2.6	206112
SPM 157	1x (4.213-4.370)	6.181 - 6.339	2.7	153092
SPM 168	1x (4.449-4.606)	6.614 - 6.772	3.4	153096
SPM 178	1x (4.843-5.000)	7.008 - 7.165	3.8	167595
SPM 188	1x (5.157-5.315)	7.402 - 7.559	4.2	167596
SPM 196	1x (5.453-5.630)	7.717 - 7.874	4.2	153100
SPM 217	1x (6.181-6.378)	8.543 - 8.701	5.2	167597
SPM 226	1x (6.575-6.732)	8.898 - 9.055	5.2	153104
SPM 266	1x (8.110-8.268)	10.472 - 10.63	6.3	206124
SPM 279	1x (8.583-8.740)	10.984 - 11.142	7.3	153036

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

The NAREE products are oriered and solid in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/ We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-30