



# Roxtec H3 -tiiviste

Avattava läpivienti kaapelien/putkien tiivistämiseen.

Roxtec H3 on pyöreä tiiviste kaapeli- ja putkiläpivienteihin metalliholkeissa tai poratuissa aukoissa. Tiivisteeseen muuttettavan rakenteen ansiosta se on helppo asentaa kaapeleiden ja putkien ympärille kolmioasennuksiin. Läpiviennin liitososa on haponkestävästä ruostumattomasta teräksestä ja sopii erikokoisiin kaapeleihin ja putkiin. Tiivistettä on saatavana myös pienemmillä heloilla aukkoon kiinnittämiseksi.



- Jyrsijäsuojattu
- Erinomainen jälkiasennuksiin
- Helppo ja nopea asennus

## Tuotteen ominaisuudet



Paloluokiteltu



Vesitiivis



Kaasutiivis



IP/UL NEMA

## Asennusrakenne



Metalli



Betoni

## Asennustyyppi



Olemassa oleva reikä



Olemassa oleva holkki

## Luokitukset ja sertifiointit

### Paloluokka


- A-luokka IMO 2010 -standardin palokoeoodin (IMO 2010 FTP Code) mukaan
- E/EI-luokitus standardin EN 13501 mukaan

### Tiiviyys

- Kaasutiiviyys: 2,67 bar (katastrofi)
- Vesitiiviyys: 4 bar (katastrofi)
- IP 68

## Tiivistyskomponenttien tiedot

### Tiivistyskomponentit



H3 -tiiviste




Roxtec-asennusrasva

Lisätietoja on osoitteessa [roxtec.com](https://www.roxtec.com).




# Valmiiksi määritetyt läpivientisarjat


mm/kg




H3-150




H3-150 WOC




H3-150 INSERTABLE




H3-150 INSERTABLE  
WOC




H3-200



H3-200 WOC



H3-200 INSERTABLE



H3-200 INSERTABLE  
WOC

Otsikko	Kokoonpano	Aukon mitat Ø	Paino	Tuotenro
H3-150	3x (24.0-54.0)	150 - 152	2.8	122905
H3-150 WOC	3x (24.0-54.0)	150 - 152	2.8	122906
H3-150 INSERTABLE	3x (24.0-54.0)	150 - 152	2.7	122907
H3-150 INSERTABLE WOC	3x (24.0-54.0)	150 - 152	2.6	122908
H3-200	3x (48.0-70.0)	200 - 202	4.8	122909
H3-200 WOC	3x (48.0-70.0)	200 - 202	4.4	122910
H3-200 INSERTABLE	3x (48.0-70.0)	200 - 202	4.7	122911
H3-200 INSERTABLE WOC	3x (48.0-70.0)	200 - 202	4.1	122912

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-06