



Vedação Roxtec H3

moldura bipartida para vedação ao redor de cabos/tubulações.

A vedação Roxtec H3 é uma vedação circular para passagens de cabo e tubo em luvas metálicas ou em passagens com furo circular. A construção dividida da vedação facilita a instalação em torno de cabos ou tubos existentes ou cabos em formação trifólia. A vedação tem conexões de aço inoxidável à prova de ácido e é ajustável a diferentes tamanhos de cabos e tubos. A vedação está disponível também para conexões frontais menores para permitir a inserção em buracos.



- Resistente a roedores
- Perfeito para retrofit/manutenção
- Rápido e fácil de instalar

Características do produto



Certificado contra fogo



À prova d'água



À prova de gás



IP/UL NEMA

Estrutura da instalação



Metal



Concreto

Tipo de montagem



Abertura existente



Luva existente

Classificações e certificados

Fogo


- A-CLASS de acordo com o Código FTP IMO 2010
- Classificação E/EI de acordo com EN 13501

Proteção contra vazamento

- Gás: 2,67 bar (catastrófico)
- Água: 4 bar (catastrófico)
- IP 68

Dados de componente de vedação

Componentes de vedação



Vedação H3




Lubrificante Roxtec

Para obter informações detalhadas, acesse [roxtec.com](https://www.roxtec.com).




Kits de passagem pré-configurada


mm/kg




H3-150




H3-150 WOC




H3-150 INSERTABLE




H3-150 INSERTABLE
WOC




H3-200



H3-200 WOC



H3-200 INSERTABLE



H3-200 INSERTABLE
WOC

Título	Configuração	Dimensões da abertura Ø	Peso	Art. No.
H3-150	3x (24.0-54.0)	150 - 152	2.8	122905
H3-150 WOC	3x (24.0-54.0)	150 - 152	2.8	122906
H3-150 INSERTABLE	3x (24.0-54.0)	150 - 152	2.7	122907
H3-150 INSERTABLE WOC	3x (24.0-54.0)	150 - 152	2.6	122908
H3-200	3x (48.0-70.0)	200 - 202	4.8	122909
H3-200 WOC	3x (48.0-70.0)	200 - 202	4.4	122910
H3-200 INSERTABLE	3x (48.0-70.0)	200 - 202	4.7	122911
H3-200 INSERTABLE WOC	3x (48.0-70.0)	200 - 202	4.1	122912

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/> We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-06