



Prostup Roxtec CF 8/32 Ex

Hliníkový vstup s vysokou prostorovou hustotou kabelů pro skříně.

Roxtec CF 8 Ex a CF 32 Ex jsou kabelové a potrubní prostupy s litými hliníkovými rámy. Vstupní těsnění jsou certifikována pro prostředí Ex e a Ex tb při teplotách -40 až +80 °C a lze je používat pro pancéřové kabely vyžadující pospojování a uzemnění. Izolační moduly jsou upravitelné pro kabely a trubky různých velikostí.

- Odolné proti hlodavcům
- Odlehčené
- Kompaktní



Vlastnosti výrobku



IP/UL NEMA



Certifikace Ex



Elektrická bezpečnost

Struktura instalace



Skříně a rozváděče

Specifikace a certifikáty

Těsnost

- IP 66/67, UL/NEMA 4,4X,12,13

Podporuje

- Pospojování a uzemnění
- Certifikace Ex

Rozměry rámu

mm/kg

Níže uvedené verze ráků jsou pouze některé možnosti. Úplnou nabídku ráků a konfigurací najdete na stránkách [roxtec.com](https://www.roxtec.com).

Název	Otvory ráků	Prostor utěsnění	Vnější rozměry WxHxD	Rozměry otvoru w x h	Hmotnost Typ. č.
CF 32 Ex	2	40 x 160	130 x 230 x 60	110(+0.5/-0.5) x 216(+0.5/-0.5)	1.2 EXCSF0000320035
CF 8 Ex	1	40 x 80	75 x 140 x 60	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.44 EXCSF0000080035

Údaje o izolačních komponentách


Těsnící komponenty



Modul CM Ex s technologií Multidiameter™



Plný kompenzační modul CM Ex



Modul CM BG™ s technologií Multidiameter™



Mazivo Roxtec

Podrobné informace najdete na stránkách www.roxtec.com.



Konfigurované soupravy přístupů

mm/kg



CF 8/8 Ex



CF 32/20 Ex



CF 32/32 Ex



CF 8/8 BG B Ex



CF 32/20 BG B Ex



CF 32/32 BG B Ex

Název	Konfigurace	Vnější rozměry WxHxD	Rozměry otvoru w x h	Hmotnost Typ. č.
CF 8/8 Ex	8x (3.5-16.5)	75 x 140 x 59	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.9 EXCKT80000008
CF 32/20 Ex	4x (9.5-32.5), 16x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.2 EXCKT32000020
CF 32/32 Ex	32x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	1.8 EXCKT32000032
CF 8/8 BG B Ex	8x (3.5-16.5)	75 x 140 x 59	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.8 103591
CF 32/20 BG B Ex	4x (9.5-32.5), 16x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.5 103736
CF 32/32 BG B Ex	32x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.4 103737

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-17