



Roxtec CF 8/32 Ex transit

High cable density aluminum transit for enclosures.

The Roxtec CF 8 Ex and CF 32 Ex are cable and pipe transits with frames of cast aluminum. The entry seals are certified for Ex e and Ex tb areas in temperatures from -40 to +80°C and can be used with armored cables that require bonding and grounding. The sealing modules are adaptable to cables and pipes of different sizes.

- Rodent resistant
- Light-weight
- Area efficient



Product characteristics



IP/UL NEMA



Ex rated



Electrical safety

Structure of installation



Cabinets & enclosures

Ratings & certificates

Tightness

- IP 66/67 according to IEC 60529, UL/NEMA 4,4X,12,13

Supports

- Bonding and grounding
- Ex rated

Frame dimensions


mm/kg

The frame variants below are a limited selection. For the full range of frames and configurations, please visit [roxtec.com](https://www.roxtec.com).

| Product | Frame openings | Packing space | External dimensions WxHxD | Aperture dimensions w x h | Weight | Art. no |
|----------|----------------|---------------|------------------------------|---------------------------------|--------|-----------------|
| CF 32 Ex | 2 | 40 x 160 | 130 x 230 x 60 | 110(+0.5/-0.5) x 216(+0.5/-0.5) | 1.2 | EXCSF0000320035 |
| CF 8 Ex | 1 | 40 x 80 | 75 x 140 x 60 | 61(+0.5/-0.5) x 127(+0.5/-0.5) | 0.44 | EXCSF0000080035 |

Sealing components

Sealing components




CM Ex module with Multidiameter™



CM Ex solid compensation module



Lubricant









CM BG™ Ex module with Multidiameter™

For detailed information, please visit [roxtec.com](https://www.roxtec.com).



Pre-configured transit kits

mm/kg

|  |  |  |  |  |  |
|--|---|---|---|---|--|
| CF 8/8 BG B Ex | CF 32/20 BG B Ex | CF 32/32 BG B Ex | CF 8/8 Ex | CF 32/20 Ex | CF 32/32 Ex |
| Product | Configuration | External dimensions WxHxD | Aperture dimensions w x h | Weight | Art. no |
| CF 8/8 BG B Ex | 8x (3.5-16.5) | 75 x 140 x 59 | 61(+0.5/-0.5) x 127(+0.5/-0.5) | 0.8 | 103591 |
| CF 32/20 BG B Ex | 4x (9.5-32.5), 16x (3.5-16.5) | 130 x 230 x 59 | 110(+0.5/-0.5) x 216(+0.5/-0.5) | 2.5 | 103736 |
| CF 32/32 BG B Ex | 32x (3.5-16.5) | 130 x 230 x 59 | 110(+0.5/-0.5) x 216(+0.5/-0.5) | 2.4 | 103737 |
| CF 8/8 Ex | 8x (3.5-16.5) | 75 x 140 x 59 | 61(+0.5/-0.5) x 127(+0.5/-0.5) | 0.9 | EXCKT80000008 |
| CF 32/20 Ex | 4x (9.5-32.5), 16x (3.5-16.5) | 130 x 230 x 59 | 110(+0.5/-0.5) x 216(+0.5/-0.5) | 2.2 | EXCKT32000020 |
| CF 32/32 Ex | 32x (3.5-16.5) | 130 x 230 x 59 | 110(+0.5/-0.5) x 216(+0.5/-0.5) | 1.8 | EXCKT32000032 |

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-07-03