



Roxtec CF 8/32 Ex - läpivienti

Alumiiniläpivienti korkeatiheyksiin kaappiasennuksiin.

Roxtec CF 8 Ex ja CF 32 Ex ovat kaapeli- ja putkiläpivientejä, joiden kehykset ovat valualumiinista. Läpivientitiivisteet on luokiteltu Ex e- ja Ex tb -alueille -40+80° C lämpötiloihin ja niitä voidaan käyttää potentiaalintasausta ja maadoitusta vaativien armeerattujen kaapeleiden kanssa. Tiivistysmoduulit sopivat erikokoisiin kaapeleihin ja putkiin.

- Jyrsijäsuojattu
- Kevyt
- Tilatehokas



Tuotteen ominaisuudet



IP/UL NEMA



Ex-kuokiteltu



Sähköturvallisuus

Asennusrakenne



Kaapit ja kotelot

Luokitukset ja sertifiointit

Tiiviys

- IP 66/67, UL/NEMA 4,4X,12,13

Tuki

- Potentialintasausta ja maadoitus
- Ex-kuokiteltu

Kehyksen mitat


mm/kg

Alla olevat kehysvaihtoehdot ovat vain osa valikoimastamme. Kattava valikoima kehyksiä ja kokoonpanoja löytyy osoitteesta [roxtec.com](https://www.roxtec.com).

Otsikko	Kehysaukot	Pakkaustila	Ulkomitat WxHxD	Aukon mitat w x h	Paino	Tuoteno
CF 32 Ex	2	40 x 160	130 x 230 x 60	110(+0.5/-0.5) x 216(+0.5/-0.5)	1.2	EXCSF0000320035
CF 8 Ex	1	40 x 80	75 x 140 x 60	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.44	EXCSF0000080035

Tiivistyskomponenttien tiedot


Tiivistyskomponentit



CM Ex -moduuli
Multidiameter™-teknologialla



CM Ex -umpimoduuli



CM BG™ Ex -moduuli
Multidiameter™-teknologialla



Roxtec-asennusrasva

Lisätietoja on osoitteessa [roxtec.com](https://www.roxtec.com).



Valmiiksi määritetyt läpivientisarjat

mm/kg



CF 8/8 Ex



CF 32/20 Ex



CF 32/32 Ex



CF 8/8 BG B Ex



CF 32/20 BG B Ex



CF 32/32 BG B Ex

Otsikko	Kokoonpano	Ulkomitat WxHxD	Aukon mitat w x h	Paino	Tuotenumero
CF 8/8 Ex	8x (3.5-16.5)	75 x 140 x 59	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.9	EXCKT80000008
CF 32/20 Ex	4x (9.5-32.5), 16x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.2	EXCKT32000020
CF 32/32 Ex	32x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	1.8	EXCKT32000032
CF 8/8 BG B Ex	8x (3.5-16.5)	75 x 140 x 59	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.8	103591
CF 32/20 BG B Ex	4x (9.5-32.5), 16x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.5	103736
CF 32/32 BG B Ex	32x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.4	103737

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-20