



Roxtec CF 8/32 Ex 트랜짓

인클로저에 사용하는 고밀도 알루미늄

Roxtec CF 8 Ex 및 CF 32 Ex는 주조 알루미늄 프레임에 갖춘 케이블 및 파이프 관통 장비입니다. 이 인입구 씰은 온도 범위가 -40 ~ +80°C인 Ex e 및 Ex tb 환경에 맞게 인증되었으며, 본딩 (Bonding) 및 접지(Grounding)가 요구되는 외장 케이블에 사용할 수 있습니다. 씰링 모듈은 다양한 규격의 케이블 및 파이프에 적용할 수 있습니다.

- 설치류 차단
- 경량
- 공간 효율성



제품 특징점



IP/UL NEMA



Ex 등급



전기관련

설치 구조



캐비닛 및 인클로저

등급 및 인증

강도

- IP 66/67, UL/NEMA 4,4X,12,13

지원

- Bonding과 Grounding
- Ex 등급

프레임 치수

mm/kg

아래의 프레임 변화는 제한된 선택입니다. 프레임 및 구성의 전체 범위를 보려면 [roxtec.com](https://www.roxtec.com)을 방문하십시오.

구성	프레임 입구	모듈설치공간	외부 치수 WxHxD	홀 치수 w x h	무게	Art. 번호
CF 32 Ex	2	40 x 160	130 x 230 x 60	110(+0.5/-0.5) x 216(+0.5/-0.5)	1.2	EXCSF0000320035
CF 8 Ex	1	40 x 80	75 x 140 x 60	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.44	EXCSF0000080035

씰링 컴포넌트 데이터


씰링 컴포넌트



CM Ex 모듈(M ultidiameter)



CM Ex 솔리드



CM BG™ Ex 모듈(Multidi ameter™ 포함)



윤활제

자세한 내용은 [roxtec.com](https://www.roxtec.com)을 방문하십시오.



키트 구성의 관통장비

mm/kg



CF 8/8 Ex



CF 32/20 Ex



CF 32/32 Ex



CF 8/8 BG B Ex



CF 32/20 BG B Ex



CF 32/32 BG B Ex

구성	구성	외부 치수 WxHxD	홀 치수 w x h	무게	Art. 번호
CF 8/8 Ex	8x (3.5-16.5)	75 x 140 x 59	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.9	EXCKT80000008
CF 32/20 Ex	4x (9.5-32.5), 16x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.2	EXCKT32000020
CF 32/32 Ex	32x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	1.8	EXCKT32000032
CF 8/8 BG B Ex	8x (3.5-16.5)	75 x 140 x 59	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.8	103591
CF 32/20 BG B Ex	4x (9.5-32.5), 16x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.5	103736
CF 32/32 BG B Ex	32x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.4	103737

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-09