



Roxtec CF 8/32 Ex-genomföring

Aluminiumgenomföring för kapslingar med hög kabeldensitet.

Roxtec CF 8 Ex och CF 32 Ex är kabel- och rör genomföringar med ramar av gjuten aluminium. Genomföringarna är certifierade för Ex e- och Ex tb-områden i temperaturer från -40 °C till +80 °C och kan användas med armerade kablar som kräver potentialutjämning och skyddsjordning. Tätningsmodulerna kan anpassas till kablar och rör i olika storlekar.

- Gnagarresistent
- Låg vikt
- Utrymmeseffektiv



Produktegenskaper



IP/UL NEMA



Ex-klassad



Elsäkerhet

Konstruktion för installation



Skåp & kapslingar

Klassningar & certifikat

Täthet

- IP 66/67, UL/NEMA 4,4X,12,13

Stödjer

- Potentialutjämning och skyddsjordning
- Ex-klassad

Ramdimensioner


mm/kg

Ramvarianterna nedan är ett begränsat urval. Du hittar hela utbudet av ramar och konfigurationer på [roxtec.com](https://www.roxtec.com).

Titel	Ramöppningar	Packningsutrymme	Ytermått WxHxD	Öppningens mått w x h	Vikt	Art. nr
CF 32 Ex	2	40 x 160	130 x 230 x 60	110(+0.5/-0.5) x 216(+0.5/-0.5)	1.2	EXCSF0000320035
CF 8 Ex	1	40 x 80	75 x 140 x 60	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.44	EXCSF0000080035

Information om tätningskomponenter


Tätningskomponenter



CM Ex-modul med Multidiameter™



CM Ex solid kompensationsmodul



CM BG™ Ex-modul med Multidiameter™



smörjmedel

Detaljerad information finns på [roxtec.com](https://www.roxtec.com).



Förkonfigurerade genomföringskit

mm/kg



CF 8/8 Ex



CF 32/20 Ex



CF 32/32 Ex



CF 8/8 BG B Ex



CF 32/20 BG B Ex



CF 32/32 BG B Ex

Titel	Konfigurering	Yttermått WxHxD	Öppningens mått w x h	Vikt	Art. nr
CF 8/8 Ex	8x (3.5-16.5)	75 x 140 x 59	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.9	EXCKT80000008
CF 32/20 Ex	4x (9.5-32.5), 16x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.2	EXCKT32000020
CF 32/32 Ex	32x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	1.8	EXCKT32000032
CF 8/8 BG B Ex	8x (3.5-16.5)	75 x 140 x 59	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.8	103591
CF 32/20 BG B Ex	4x (9.5-32.5), 16x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.5	103736
CF 32/32 BG B Ex	32x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.4	103737

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-18