



# Roxtec CF 8/32 防爆穿隔系统

用于箱柜的高电缆密度铝制穿隔系统。

Roxtec CF 8 Ex 和 CF 32 Ex 是带铸铝框架的电缆和管道穿隔系统。该穿隔密封系统经认证可用于 Ex e 和 Ex tb 区域于工作温度为 -40 到 +80°C 于并可与需要接地的铠装电缆配合使用。其密封模块能够灵活适配各种规格的电缆/管道。

- 防啮齿动物
- 轻型
- 节省空间



## 产品特性



IP/UL NEMA



防爆等级



电气安全

## 安装结构



箱柜和机柜

## 等级和证书

### 密封性

- IP 66/67, UL/NEMA 4,4X,12,13

### 支持

- 连接和接地
- 防爆等级

## 框架尺寸

mm/kg

下方的不同框架只是部分选择。要了解全部的框架和配置于请访问 [roxtec.com](https://www.roxtec.com)。

标题	框架开口	密封空间	外部尺寸 WxHxD	开孔尺寸 w x h	重量	产品编号
CF 32 Ex	2	40 x 160	130 x 230 x 60	110(+0.5/-0.5) x 216(+0.5/-0.5)	1.2	EXCSF0000320035
CF 8 Ex	1	40 x 80	75 x 140 x 60	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.44	EXCSF0000080035

## 密封组件数据


### 密封组件



Multidiameter™ 多径 CM 防爆模块



CM 防爆盲堵模块



Multidiameter™ 多径 CM BG™ 防爆模块




润滑脂

如需了解详细信息于请访问 [roxtec.com](https://www.roxtec.com)。



# 预装配的穿隔套件

mm/kg



标题	配置	外部尺寸 WxHxD	开孔尺寸 w x h	重量	产品编号
CF 8/8 Ex	8x (3.5-16.5)	75 x 140 x 59	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.9	EXCKT80000008
CF 32/20 Ex	4x (9.5-32.5), 16x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.2	EXCKT32000020
CF 32/32 Ex	32x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	1.8	EXCKT32000032
CF 8/8 BG B Ex	8x (3.5-16.5)	75 x 140 x 59	61(+0.5/-0.5) x 127(+0.5/-0.5)	0.8	103591
CF 32/20 BG B Ex	4x (9.5-32.5), 16x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.5	103736
CF 32/32 BG B Ex	32x (3.5-16.5)	130 x 230 x 59	110(+0.5/-0.5) x 216(+0.5/-0.5)	2.4	103737

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-20