





# **Roxtec R EMC transit**

Round transit for EMC, for area efficient sealing of multiple cables and pipes.

The Roxtec R EMC is a cable and pipe transit ensuring electromagnetic compatibility. The transit frame is designed to be installed into conductive pipe sleeves. The compression is integrated in the frame and it seals by expansion. There is a choice between Roxtec ES modules for electromagnetic shielding or PE modules that protect against conducted disturbances. The modules adapt to cables and pipes of different sizes, and can be used to build in spare capacity in the transit. Roxtec EC (electrical continuity) test sticks are available to help indicate the electrical performance of the transit installation.





Easy to maintain and inspect


#### **Product characteristics**













Meta

Mounting type



Existing sleeve

## **Ratings & certificates**

### Fire

- A-CLASS according to IMO 2010 FTP
  Code
- E/El rating according to EN 13501
- F/T rating according to UL 1479
- H-CLASS according to IMO 2010 FTP Code + HC fire load curve

### **Tightness**

- Gas: 2.5 bar (catastrophic)
- Water: 4 bar (catastrophic)

### **Supports**

- Electromagnetic shielding
- Potential equalization

### Frame dimensions

### in/lbs

The frame variants below are a limited selection. For the full range of frames and configurations, please visit roxtec.com.

Product	Packing space	Aperture dimensions	Weight	Art. no
R 75 EMC AISI316	1.575 x 1.575	2.953 - 3.031	1.1	ER00A00751121
R 100 EMC AISI316	2.362 x 2.362	3.937 - 4.016	1.8	ER00A01001121
R 125 EMC AISI316	3.15 x 3.15	4.921 - 5	2.1	5ER0000004913
R 127 EMC AISI316	3.15 x 3.15	5 - 5.079	2.2	ER00A01271121
R 150 EMC AISI316	3.543 x 3.543	5.906 - 5.984	3.7	ER00A01501121
R 70 EMC AISI316	1.575 x 1.575	2.756 - 2.835	1	ER00A00701121
R 200 EMC AISI316	4.724 × 4.724	7.874 - 7.953	5.9	ER00A02001121

1/2 2024-04-29



https://www.roxtec.com/linktransit/en-us/solution/18550



### **Sealing components**

### **Sealing components**







Lubricant



RM ES solid compensation



RM PE module with Multidiameter™



RM PE solid compensation module

#### **Accessories**



Accessories ES and BG



R ES sealing kit

For detailed information, please visit roxtec.com.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

the intended process, installation and/or use.
Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.
Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect,

consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-29

2/2 2024-04-29