



Sello Roxtec ComSeal™ EMC

Sello de entrada de cables con calificación IP 54 para EMC.

Roxtec ComSeal™ EMC cuenta con la calificación IP 54 y está diseñado para garantizar la compatibilidad electromagnética. El sello está disponible con marco de aluminio niquelado. Hay una opción entre los módulos Roxtec ES para blindajes electromagnéticos y los módulos PE que protegen frente a las perturbaciones conducidas. Los módulos se adaptan a cables de diferentes tamaños. El sello está disponible en seis tamaños diferentes que admiten de 4 a 32 cables.



- Resistente a roedores
- Ligero
- Eficiencia de área
- Permite cables precabados
- Ofrece capacidad de repuesto incorporada
- Se adapta a cables y tuberías de diferentes tamaños

Características del producto



IP/UL NEMA



Protección contra EMI

Estructura de instalación



Armarios envolventes & prefabricados

Calificaciones y certificados

Estanquidad

- IP 54 según IEC 60529, UL/NEMA 3,12,12K

Soportes

- Apantallamiento electromagnético
- Ecualización de potencia

Datos de los componentes de sellado

Componentes de sellado



Gel de montaje Roxtec

Para obtener información detallada, visite [roxtec.com](https://www.roxtec.com).




Kits de sellos preconfigurados


mm/kg



ComSeal 10/4 ES




ComSeal 10/7 ES




ComSeal 10/10 ES



ComSeal 12/3 ES




ComSeal 12/6 ES




ComSeal 12/9 ES




ComSeal 12/12 ES



ComSeal 15/3 ES




ComSeal 16/4 ES



ComSeal 16/7 ES




ComSeal 16/10 ES




ComSeal 16/16 ES




ComSeal 30/6 ES




ComSeal 32/8 ES




ComSeal 32/14 ES




ComSeal 32/20 ES




ComSeal 32/32 ES




ComSeal 10/4 PE



ComSeal 10/7 PE



ComSeal 10/10 PE



ComSeal 12/3 PE




ComSeal 12/6 PE




ComSeal 12/9 PE




ComSeal 12/12 PE




ComSeal 15/3 PE



ComSeal 16/4 PE




ComSeal 16/7 PE




ComSeal 16/10 PE




ComSeal 16/16 PE




ComSeal 32/8 PE



ComSeal 32/14 PE



ComSeal 32/20 PE



ComSeal 32/32 PE



Título	Configuración	Dimensiones externas WxHxD	Dimensiones de abertura w x h	Peso	N.º de art.
ComSeal 10/4 ES	2x (3.5-16.5), 2x (9.5-32.5)	81 x 173 x 55	56(+1/-1) x 149(+1/-1)	0.6	CSE0000000104
ComSeal 10/7 ES	6x (3.5-16.5), 1x (9.5-32.5)	81 x 173 x 55	56(+1/-1) x 149(+1/-1)	0.6	CSE0000000107
ComSeal 10/10 ES	10x (3.5-16.5)	81 x 173 x 55	56(+1/-1) x 149(+1/-1)	0.6	CSE00000001010
ComSeal 12/3 ES	3x (9.5-32.5)	88 x 216 x 55	56(+1/-1) x 169(+1/-1)	0.8	CSE00000001203
ComSeal 12/6 ES	4x (3.5-16.5), 2x (9.5-32.5)	88 x 216 x 55	56(+1/-1) x 169(+1/-1)	0.8	CSE00000001206
ComSeal 12/9 ES	8x (3.5-16.5), 1x (9.5-32.5)	88 x 216 x 55	56(+1/-1) x 169(+1/-1)	0.8	CSE00000001209
ComSeal 12/12 ES	12x (3.5-16.5)	88 x 216 x 55	56(+1/-1) x 169(+1/-1)	0.8	CSE00000001212
ComSeal 15/3 ES	3x (28.0-44.0)	91 x 223 x 55	61(+1/-1) x 195(+1/-1)	0.9	CSE00000001503
ComSeal 16/4 ES	4x (9.5-32.5)	81 x 233 x 55	56(+1/-1) x 209(+1/-1)	0.9	CSE0000000164
ComSeal 16/7 ES	4x (3.5-16.5), 3x (9.5-32.5)	81 x 233 x 55	56(+1/-1) x 209(+1/-1)	0.9	CSE0000000167
ComSeal 16/10 ES	8x (3.5-16.5), 2x (9.5-32.5)	81 x 233 x 55	56(+1/-1) x 209(+1/-1)	0.9	CSE00000001610
ComSeal 16/16 ES	16x (3.5-16.5)	81 x 233 x 55	56(+1/-1) x 209(+1/-1)	0.9	CSE00000001616
ComSeal 30/6 ES	6x (28.0-44.0)	155 x 231 x 55	120(+1/-1) x 195(+1/-1)	1.6	CSE00000003006
ComSeal 32/8 ES	8x (9.5-32.5)	135 x 241 x 55	103(+1/-1) x 209(+1/-1)	1.4	CSE00000003208
ComSeal 32/14 ES	8x (3.5-16.5), 6x (9.5-32.5)	135 x 241 x 55	103(+1/-1) x 209(+1/-1)	1.6	CSE00000003214
ComSeal 32/20 ES	16x (3.5-16.5), 4x (9.5-32.5)	135 x 241 x 55	103(+1/-1) x 209(+1/-1)	1.5	CSE00000003220
ComSeal 32/32 ES	32x (3.5-16.5)	135 x 241 x 55	103(+1/-1) x 209(+1/-1)	1.5	CSE00000003232
ComSeal 10/4 PE	2x (3.5-16.5), 2x (9.5-32.5)	81 x 173 x 33	56(+1/-1) x 149(+1/-1)	0.7	CSP0000000104
ComSeal 10/7 PE	6x (3.5-16.5), 1x (9.5-32.5)	81 x 173 x 33	56(+1/-1) x 149(+1/-1)	0.6	CSP0000000107
ComSeal 10/10 PE	10x (3.5-16.5)	81 x 173 x 33	56(+1/-1) x 149(+1/-1)	0.46	CSP00000001010
ComSeal 12/3 PE	3x (9.5-32.5)	88 x 216 x 33	56(+1/-1) x 169(+1/-1)	0.8	CSP00000001203
ComSeal 12/6 PE	4x (3.5-16.5), 2x (9.5-32.5)	88 x 216 x 33	56(+1/-1) x 169(+1/-1)	0.8	CSP00000001206
ComSeal 12/9 PE	8x (3.5-16.5), 1x (9.5-32.5)	88 x 216 x 33	56(+1/-1) x 169(+1/-1)	0.8	CSP00000001209
ComSeal 12/12 PE	12x (3.5-16.5)	88 x 216 x 33	56(+1/-1) x 169(+1/-1)	0.8	CSP00000001212
ComSeal 15/3 PE	3x (28.0-44.0)	81 x 223 x 33	61(+1/-1) x 195(+1/-1)	0.9	CSP00000001503
ComSeal 16/4 PE	4x (9.5-32.5)	81 x 233 x 33	56(+1/-1) x 209(+1/-1)	0.8	CSP0000000164
ComSeal 16/7 PE	4x (3.5-16.5), 3x (9.5-32.5)	81 x 233 x 33	56(+1/-1) x 209(+1/-1)	0.8	CSP0000000167
ComSeal 16/10 PE	8x (3.5-16.5), 2x (9.5-32.5)	81 x 233 x 33	56(+1/-1) x 209(+1/-1)	0.8	CSP00000001610
ComSeal 16/16 PE	16x (3.5-16.5)	81 x 233 x 33	56(+1/-1) x 209(+1/-1)	0.8	CSP00000001616
ComSeal 30/6 PE	6x (28.0-44.0)	155 x 231 x 33	120(+1/-1) x 195(+1/-1)	1.6	CSP00000003006
ComSeal 32/8 PE	8x (9.5-32.5)	135 x 241 x 33	103(+1/-1) x 209(+1/-1)	1.5	CSP00000003208
ComSeal 32/14 PE	8x (3.5-16.5), 6x (9.5-32.5)	135 x 241 x 33	103(+1/-1) x 209(+1/-1)	1.5	CSP00000003214
ComSeal 32/20 PE	16x (3.5-16.5), 4x (9.5-32.5)	135 x 241 x 33	103(+1/-1) x 209(+1/-1)	1.5	CSP00000003220
ComSeal 32/32 PE	32x (3.5-16.5)	135 x 241 x 33	103(+1/-1) x 209(+1/-1)	1.5	CSP00000003232

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2025-07-03



Roxtec ® and Multidiameter ®
are registered trademarks of Roxtec
in Sweden and/or other countries.