



Passage Roxtec ComSeal™ EMC

Passage de câbles étanche et certifié IP 54 pour la CEM.

Le Roxtec ComSeal™ CEM est certifié IP 54 et il est conçu pour garantir la compatibilité électromagnétique. Le ComSeal™ CEM est disponible avec un cadre en aluminium nickelé. Il existe des modules Roxtec ES pour le blindage électromagnétique et des modules PE qui offrent une protection contre les perturbations conduites. Les modules s'adaptent à différentes tailles de câbles. Le passage est disponible dans six tailles différentes pour accueillir 4 à 32 câbles.



- Résistant aux rongeurs
- Léger
- Surface optimisée
- Accepte des câbles pré-connectés
- Fournit une capacité de réserve intégrée
- S'adapte à différents diamètres de câbles et de tuyaux

Caractéristiques du produit



IP/UL NEMA



Protection IEM

Structure d'installation



Armoires et coffrets

Classements et certificats

Étanchéité

- IP 54 selon IEC 60529, IP 55 selon IEC 60529, UL/NEMA 3,12,12K

Supports

- Blindage électromagnétique

Éléments d'étanchéité

Éléments d'étanchéité



Gel d'assemblage Roxtec

Pour plus d'informations, veuillez consulter [roxtec.com](https://www.roxtec.com).

Kits de passage préconfigurés

mm/kg



Nom	Capacité (quantité x taille)	Dimensions externes LxHxP (mm)	Poids (kg) N° art.
ComSeal 10/4 ES	2x (3.5-16.5) 2x (9.5-32.5)	80.5 x 173 x 55	0.65 CSE0000000104
ComSeal 10/7 ES	6x (3.5-16.5) 1x (9.5-32.5)	80.5 x 173 x 55	0.63 CSE0000000107
ComSeal 10/10 ES	10x (3.5-16.5)	80.5 x 173 x 55	0.65 CSE00000001010
ComSeal 12/3 ES	3x (9.5-32.5)	88 x 216 x 55	0.84 CSE00000001203
ComSeal 12/6 ES	4x (3.5-16.5) 2x (9.5-32.5)	88 x 216 x 55	0.82 CSE00000001206
ComSeal 12/9 ES	8x (3.5-16.5) 1x (9.5-32.5)	88 x 216 x 55	0.8 CSE00000001209
ComSeal 12/12 ES	12x (3.5-16.5)	88 x 216 x 55	0.82 CSE00000001212
ComSeal 15/3 ES	3x (28.0-44.0)	80.5 x 223 x 55	0.88 CSE00000001503
ComSeal 16/4 ES	4x (9.5-32.5)	80.5 x 233 x 55	0.87 CSE00000000164
ComSeal 16/7 ES	4x (3.5-16.5) 3x (9.5-32.5)	80.5 x 233 x 55	0.91 CSE00000000167
ComSeal 16/10 ES	8x (3.5-16.5) 2x (9.5-32.5)	80.5 x 233 x 55	0.86 CSE000000001610
ComSeal 16/16 ES	16x (3.5-16.5)	80.5 x 233 x 55	0.87 CSE000000001616
ComSeal 30/6 ES	6x (28.0-44.0)	155 x 231 x 55	1.63 CSE000000003006
ComSeal 32/8 ES	8x (9.5-32.5)	135 x 241 x 55	1.41 CSE000000003208
ComSeal 32/14 ES	8x (3.5-16.5) 6x (9.5-32.5)	135 x 241 x 55	1.57 CSE000000003214
ComSeal 32/20 ES	16x (3.5-16.5) 4x (9.5-32.5)	135 x 241 x 55	1.5 CSE000000003220
ComSeal 32/32 ES	32x (3.5-16.5)	135 x 241 x 55	1.53 CSE000000003232

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2026-08-28

