



Roxtec ComSeal™ EMC 貫通部

IP 54のEMC対策用ケーブルシール

Roxtec ComSeal™ EMCは、IP 54の保護等級で、電磁両立性を確保できるデザインです。シールはニッケルメッキアルミニウム製のフレームと併せてご使用いただけます。シーリングモジュールは、電磁遮蔽向けのRoxtec ESモジュールと、伝導妨害を防ぐPEモジュールからお選びいただけます。モジュールは様々な外径のケーブルに対応可能です。貫通部フレームは6つのから選ぶことができ、一つの貫通部で4～32本のケーブルを通しシーリングすることができます。

- 防鼠
- 軽量
- 優れた面積効率
- 端末処理済みケーブル使用可
- 予備スペースの確保
- 異なる外径のケーブル・パイプに対応可能

製品特性



IP/UL NEMA



EMI 対

設置構造



キャビネット & エンクロージ



規格と認証証明書

密性

- IEC 60529 規格 IP 54, IEC 60529 規格 IP 55, UL/NEMA 3、12、12K

サポート

- 電磁シールド

シーリングコンポーネントのデータ

シーリングコンポーネント



組立ゲル

詳細情報については、[roxtec.com](https://www.roxtec.com) をご覧ください。




設定済み貫通部キット


mm/kg



ComSeal 10/4 ES




ComSeal 10/7 ES




ComSeal 10/10 ES



ComSeal 12/3 ES




ComSeal 12/6 ES




ComSeal 12/9 ES




ComSeal 12/12 ES



ComSeal 15/3 ES




ComSeal 16/4 ES



ComSeal 16/7 ES



ComSeal 16/10 ES




ComSeal 16/16 ES




ComSeal 30/6 ES




ComSeal 32/8 ES



ComSeal 32/14 ES



ComSeal 32/20 ES



ComSeal 32/32 ES

名称	容量 (本数 x 径)	外形 WxHxD (mm)	重量 (kg)	部品番号
ComSeal 10/4 ES	2x (3.5-16.5) 2x (9.5-32.5)	80.5 x 173 x 55	0.65	CSE0000000104
ComSeal 10/7 ES	6x (3.5-16.5) 1x (9.5-32.5)	80.5 x 173 x 55	0.63	CSE0000000107
ComSeal 10/10 ES	10x (3.5-16.5)	80.5 x 173 x 55	0.65	CSE00000001010
ComSeal 12/3 ES	3x (9.5-32.5)	88 x 216 x 55	0.84	CSE00000001203
ComSeal 12/6 ES	4x (3.5-16.5) 2x (9.5-32.5)	88 x 216 x 55	0.82	CSE00000001206
ComSeal 12/9 ES	8x (3.5-16.5) 1x (9.5-32.5)	88 x 216 x 55	0.8	CSE00000001209
ComSeal 12/12 ES	12x (3.5-16.5)	88 x 216 x 55	0.82	CSE00000001212
ComSeal 15/3 ES	3x (28.0-44.0)	80.5 x 223 x 55	0.88	CSE00000001503
ComSeal 16/4 ES	4x (9.5-32.5)	80.5 x 233 x 55	0.87	CSE00000000164
ComSeal 16/7 ES	4x (3.5-16.5) 3x (9.5-32.5)	80.5 x 233 x 55	0.91	CSE00000000167
ComSeal 16/10 ES	8x (3.5-16.5) 2x (9.5-32.5)	80.5 x 233 x 55	0.86	CSE000000001610
ComSeal 16/16 ES	16x (3.5-16.5)	80.5 x 233 x 55	0.87	CSE000000001616
ComSeal 30/6 ES	6x (28.0-44.0)	155 x 231 x 55	1.63	CSE000000003006
ComSeal 32/8 ES	8x (9.5-32.5)	135 x 241 x 55	1.41	CSE000000003208
ComSeal 32/14 ES	8x (3.5-16.5) 6x (9.5-32.5)	135 x 241 x 55	1.57	CSE000000003214
ComSeal 32/20 ES	16x (3.5-16.5) 4x (9.5-32.5)	135 x 241 x 55	1.5	CSE000000003220
ComSeal 32/32 ES	32x (3.5-16.5)	135 x 241 x 55	1.53	CSE000000003232



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2026-08-28

