Roxtec

Przeczytaj więcej o rozwiązaniu na roxtec.com
https://www.roxtec.com/linktransit/pl-pl/solution/18553

Przepust Roxtec ComSeal™ EMC

Przepust zapewnia szczelność IP 54 do zastosowań EMC.

Roxtec ComSeal™ EMC zapewnia szczelność IP 54 oraz kompatybilność elektromagnetyczną. Uszczelnienie dostępne w wersji z ramą z niklowanego aluminium. Dostępne do wyboru są moduły Roxtec ES z funkcją ekranowania elektromagnetycznego lub PE chroniące przed zaburzeniami przewodzonymi. Moduły można dopasować do różnych rozmiarów kabli. Przepust jest dostępny w sześciu rozmiarach, pozwalających uszczelnić od 4 do 32 kabli.

Charakterystyka produktu

IP/UL NEMA

Ochrona EMI

Struktura podłoża instalacyjnego

Szafy i obudowy

Klasy i certyfikaty

Szczelność

- IP 54, UL/NEMA 3,12,12K

Zgodność

- Ekranowanie elektromagnetyczne
- Wyrównywanie potencjałów

Dane elementów uszczelniających

Elementy uszczelniające

Żel montażowy Roxtec

Szczegółowe informacje można znaleźć na roxtec.com.

Gotowe zestawy przepustów

mm/kg

ComSeal 10/4 ES

ComSeal 12/12 PE


ComSeal 16/7 ES


ComSeal 32/14 PE


ComSeal 16/7 PE


ComSeal 30/6 ES


ComSeal 10/10 ES


ComSeal 10/10 PE


ComSeal 10/4 PE


ComSeal 10/7 ES


ComSeal 10/7 PE


ComSeal 12/12 ES


ComSeal 12/3 PE


ComSeal 12/6 PE


ComSeal 12/9 ES

ComSeal 12/9 PE


ComSeal 15/3 ES


ComSeal 15/3 PE


ComSeal 16/16 PE


ComSeal 16/4 ES


ComSeal 16/4 PE


ComSeal 32/14 ES


ComSeal 32/20 ES


ComSeal 32/8 PE


ComSeal 32/32 PE


ComSeal 16/16 ES

ComSeal 16/10 ES


ComSeal 32/32 ES


ComSeal 32/20 PE

ComSeal 12/3 ES

ComSeal 32/8 ES


ComSeal 12/6 ES


ComSeal 16/10 PE

Tytuł	Konfiguracja	Wymiary zewnętrzne WxHxD	Wymiary otworu w x h	Waga	Nr katalogowy
ComSeal 10/4 ES	2x (3.5-16.5), 2x (9.5-32.5)	81 x 173 x 55	56(+1/-1) x 149(+1/-1)	0.6	CSE0000000104
ComSeal 12/12 PE	12x (3.5-16.5)	88 x 216 x 33	56(+1/-1) x 169(+1/-1)	0.8	CSP0000001212
ComSeal 16/7 ES	4x (3.5-16.5), 3x (9.5-32.5)	81 x 233 x 55	56(+1/-1) x 209(+1/-1)	0.9	CSE0000000167
ComSeal 32/14 PE	8x (3.5-16.5), 6x (9.5-32.5)	135 x 241 x 33	103(+1/-1) x 209(+1/-1)	1.5	CSP0000003214
ComSeal 16/7 PE	4x (3.5-16.5), 3x (9.5-32.5)	81 x 233 x 33	56(+1/-1) x 209(+1/-1)	0.8	CSP0000000167
ComSeal 30/6 ES	6x (28.0-44.0)	155 x 231 x 55	120(+1/-1) x 195(+1/-1)	1.6	CSE0000003006
ComSeal 10/10 ES	10x (3.5-16.5)	81 x 173 x 55	56(+1/-1) x 149(+1/-1)	0.6	CSE0000001010
ComSeal 10/10 PE	10x (3.5-16.5)	81 x 173 x 33	56(+1/-1) x 149(+1/-1)	0.46	CSP0000001010
ComSeal 10/4 PE	2x (3.5-16.5), 2x (9.5-32.5)	81 x 173 x 33	56(+1/-1) x 149(+1/-1)	0.7	CSP0000000104
ComSeal 10/7 ES	6x (3.5-16.5), 1x (9.5-32.5)	81 x 173 x 55	56(+1/-1) x 149(+1/-1)	0.6	CSE0000000107
ComSeal 10/7 PE	6x (3.5-16.5), 1x (9.5-32.5)	81 x 173 x 33	56(+1/-1) x 149(+1/-1)	0.6	CSP0000000107
ComSeal 12/12 ES	12x (3.5-16.5)	88 x 216 x 55	56(+1/-1) x 169(+1/-1)	0.8	CSE0000001212
ComSeal 12/3 PE	3x (9.5-32.5)	88 x 216 x 33	56(+1/-1) x 169(+1/-1)	0.8	CSP0000001203
ComSeal 12/6 PE	4x (3.5-16.5), 2x (9.5-32.5)	88 x 216 x 33	56(+1/-1) x 169(+1/-1)	0.8	CSP0000001206
ComSeal 12/9 ES	8x (3.5-16.5), 1x (9.5-32.5)	88 x 216 x 55	56(+1/-1) x 169(+1/-1)	0.8	CSE0000001209
ComSeal 12/9 PE	8x (3.5-16.5), 1x (9.5-32.5)	88 x 216 x 33	56(+1/-1) x 169(+1/-1)	0.8	CSP0000001209
ComSeal 15/3 ES	3x (28.0-44.0)	91 x 223 x 55	61(+1/-1) x 195(+1/-1)	0.9	CSE0000001503
ComSeal 15/3 PE	3x (28.0-44.0)	81 x 223 x 33	61(+1/-1) x 195(+1/-1)	0.9	CSP0000001503
ComSeal 16/16 PE	16x (3.5-16.5)	81 x 233 x 33	56(+1/-1) x 209(+1/-1)	0.8	CSP0000001616
ComSeal 16/4 ES	4x (9.5-32.5)	81 x 233 x 55	56(+1/-1) x 209(+1/-1)	0.9	CSE0000000164
ComSeal 16/4 PE	4x (9.5-32.5)	81 x 233 x 33	56(+1/-1) x 209(+1/-1)	0.8	CSP0000000164
ComSeal 32/14 ES	8x (3.5-16.5), 6x (9.5-32.5)	135 x 241 x 55	103(+1/-1) x 209(+1/-1)	1.6	CSE0000003214
ComSeal 32/20 ES	16x (3.5-16.5), 4x (9.5-32.5)	135 x 241 x 55	103(+1/-1) x 209(+1/-1)	1.5	CSE0000003220
ComSeal 32/8 PE	8x (9.5-32.5)	135 x 241 x 33	103(+1/-1) x 209(+1/-1)	1.5	CSP0000003208
ComSeal 32/32 PE	32x (3.5-16.5)	135 x 241 x 33	103(+1/-1) x 209(+1/-1)	1.5	CSP0000003232
ComSeal 16/16 ES	16x (3.5-16.5)	81 x 233 x 55	56(+1/-1) x 209(+1/-1)	0.9	CSE0000001616
ComSeal 16/10 ES	8x (3.5-16.5), 2x (9.5-32.5)	81 x 233 x 55	56(+1/-1) x 209(+1/-1)	0.9	CSE0000001610
ComSeal 30/6 PE	6x (28.0-44.0)	155 x 231 x 33	120(+1/-1) x 195(+1/-1)	1.6	CSP0000003006
ComSeal 32/32 ES	32x (3.5-16.5)	135 x 241 x 55	103(+1/-1) x 209(+1/-1)	1.5	CSE0000003232
ComSeal 32/20 PE	16x (3.5-16.5), 4x (9.5-32.5)	135 x 241 x 33	103(+1/-1) x 209(+1/-1)	1.5	CSP0000003220
ComSeal 12/3 ES	3x (9.5-32.5)	88 x 216 x 55	56(+1/-1) x 169(+1/-1)	0.8	CSE0000001203
ComSeal 32/8 ES	8x (9.5-32.5)	135 x 241 x 55	103(+1/-1) x 209(+1/-1)	1.4	CSE0000003208
ComSeal 12/6 ES	4x (3.5-16.5), 2x (9.5-32.5)	88 x 216 x 55	56(+1/-1) x 169(+1/-1)	0.8	CSE0000001206
ComSeal 16/10 PE	8x (3.5-16.5), 2x (9.5-32.5)	81 x 233 x 33	56(+1/-1) x 209(+1/-1)	0.8	CSP0000001610

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.
Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.
Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.
The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/
We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.
This document was generated on: 2024-04-29