





Roxtec G EMC transit

Transit for EMC, attached by welding.

The Roxtec G EMC is a cable and pipe seal ensuring electromagnetic compatibility. It has a steel frame for welding. There is a choice between Roxtec ES modules for electromagnetic shielding and PE modules that protect against conducted disturbances. The modules adapt to a variety of cable sizes. The transit can be used with a GE extension frame in galvanized steel to cover the depth of a thick wall. Roxtec EC (electrical continuity) test sticks are available to help indicate the electrical performance of the transit installation.



Provides built-in spare capacity



Ratings & certificates

Fire

- A-CLASS according to IMO 2010 FTP Code
- E/El rating according to EN 13501
- Tightness
- 🔘 Gas: 2.5 bar (catastrophic)
- O Water: 4 bar (catastrophic)

Supports

- Electromagnetic shielding
- Potential equalization

Frame dimensions

in/lbs


The frame variants below are a limited selection. For the full range of frames and configurations, please visit roxtec.com.

	ı — "	Product	Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
	н	G 6x1 PRIMED	1	4.724 x 7.087	9.941 x 13.78 x 2.362	7.402(+0.591/-0.591) x 11.417(+0.591/-0.591)	9.8	G00600000112
		G 6x2 PRIMED	2	4.724 x 7.087	15.079 x 13.78 x 2.362	12.52(+0.591/-0.591) x 11.417(+0.591/-0.591)	16.2	G00600000212
		G 6x3 PRIMED	3	4.724 x 7.087	20.217 x 13.78 x 2.362	17.677(+0.591/-0.591) x 11.417(+0.591/-0.591)	21.6	G00600000312
		G 6x1 AISI316	1	4.724 × 7.087	9.941 x 13.78 x 2.362	7.402(+0.591/-0.591) x 11.417(+0.591/-0.591)	10.5	G00600000121
w		G 6x2 AISI316	2	4.724 × 7.087	15.079 x 13.78 x 2.362	12.52(+0.591/-0.591) x 11.417(+0.591/-0.591)	16.1	G00600000221
		G 6x3 AISI316	3	4.724 x 7.087	20.217 x 13.78 x 2.362	17.677(+0.591/-0.591) x 11.417(+0.591/-0.591)	21.6	G00600000321





Sealing components



For detailed information, please visit roxtec.com.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

Roxtec expressly excludes any implied warranties of mechantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or

common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect,

consequential, punitive, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from

https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/ We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-27