



Roxtec SBTB EMC transit

Transit for EMC with metal frame for extra fire protection.

The Roxtec SBTB EMC is a double-sided cable and pipe transit ensuring electromagnetic compatibility and a high level of fire protection. The metal frame is welded to the structure. There is a choice between Roxtec ES modules for electromagnetic shielding and PE modules that protect against conducted disturbances. Roxtec EC (electrical continuity) test sticks are available to help indicate the electrical performance of the transit installation.





Provides built-in spare capacity

Product characteristics









Fire rated

Watertight

G

EMI protection

Structure of installation

Meta

Mounting type



Welding


Ratings & certificates

Fire

- A-CLASS according to IMO 2010 FTP Code
- H-CLASS according to IMO 2010 FTP Code + HC fire load curve
- Jet fire according to ISO 22899-1 and OTI 95634

Tightness

Gas: 2.5 bar (catastrophic)



Supports

Electromagnetic shielding

Potential equalization

Frame dimensions

in/lbs

The frame variants below are a limited selection. For the full range of frames and configurations, please visit roxtec.com.

Product	Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
SBTB 6x1 ALU	1	4.724 x 7.087	5.531 x 9.37 x 7.874	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	8.8	105587
SBTB 6x2 ALU	2	4.724 x 7.087	10.669 x 9.37 x 7.874	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	12.7	5SBT000007020
SBTB 6x3 ALU	3	4.724 x 7.087	15.807 x 9.37 x 7.874	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	17.3	105588
SBTB 6x1 PRIMED	1	4.724 x 7.087	5.531 x 9.37 x 7.874	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	23.1	5\$00000004391
SBTB 6x2 PRIMED	2	4.724 x 7.087	10.669 x 9.37 x 7.874	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	37.4	5\$00000004503
SBTB 6x3 PRIMED	3	4.724 x 7.087	15.807 x 9.37 x 7.874	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	49.2	5\$00000004393
SBTB 6x1 AISI316	1	4.724 x 7.087	5.531 x 9.37 x 7.874	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	23.9	5SBT000002149
SBTB 6x2 AISI316	2	4.724 x 7.087	10.669 x 9.37 x 7.874	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	37.3	5SBT000004538
SBTB 6x3 AISI316	3	4.724 x 7.087	15.807 x 9.37 x 7.874	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	50.3	5SBTB00010248

2024-04-27





Sealing components

Sealing components



RM ES module with



Lubricant



Wedge & Wedgekit ES



RM ES solid compensation module



RM PE module with Multidiameter

Accessories



Accessories ES and BG



Holder tools



RM PE solid compensation



Wedge & Wedgekit



Stayplate



ES sealing kit



Welding tools

For detailed information, please visit roxtec.com.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied expressions and warranties provided by statute or

common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect,

consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from

https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/
We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-27

2/2 2024-04-27