



Roxtec SBTB BG™ transit

Transit for bonding, grounding and extra fire protection.

The Roxtec SBTB $\mathsf{BG}^{\scriptscriptstyle\mathsf{TM}}$ is a double-sided cable and pipe transit for bonding, grounding and a high level of fire protection. The metal frame is welded to the structure. The Roxtec BG™ sealing modules adapt to armored and metal-clad cables and pipes of different sizes. Roxtec EC (electrical continuity) test sticks are available to help indicate the electrical performance of the transit installation.







Provides built-in spare capacity


Product characteristics













Metal

Mounting type



Welding

Ratings & certificates

Fire

A-CLASS according to IMO 2010 FTP Code

H-CLASS according to IMO 2010 FTP Code + HC fire load curve

Jet fire according to ISO 22899-1 and OTI

Tightness

Gas: 2.5 bar (catastrophic)

Water: 4 bar (catastrophic)

Supports

Bonding and grounding

Frame dimensions

The frame variants below are a limited selection. For the full range of frames and configurations, please visit roxtec.com.

Product	Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
SBTB 6x1 ALU	1	4.724 × 7.087	5.531 x 9.37 x 7.874	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	8.8	105587
SBTB 6x2 ALU	2	4.724 x 7.087	10.669 x 9.37 x 7.874	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	12.7	5SBT000007020
SBTB 6x3 ALU	3	4.724 x 7.087	15.807 x 9.37 x 7.874	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	17.3	105588
SBTB 6x1 PRIMED	1	4.724 x 7.087	5.531 x 9.37 x 7.874	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	23.1	5S00000004391
SBTB 6x2 PRIMED	2	4.724 x 7.087	10.669 x 9.37 x 7.874	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	37.4	5\$0000004503
SBTB 6x3 PRIMED	3	4.724 x 7.087	15.807 x 9.37 x 7.874	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	49.2	5\$0000004393
SBTB 6x1 AISI316	1	4.724 × 7.087	5.531 x 9.37 x 7.874	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	23.9	5SBT000002149
SBTB 6x2 AISI316	2	4.724 x 7.087	10.669 x 9.37 x 7.874	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	37.3	5SBT000004538
SBTB 6x3 AISI316	3	4.724 x 7.087	15.807 x 9.37 x 7.874	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	50.3	5SBTB00010248

2024-05-03





Sealing components

Sealing components



RM BG™ module with Multidiameter™



RM BG™ solid compensation module



BG™ sealing kit



Lubricant



Wedge & Wedgekit

Accessories





Accessories ES and BG



Welding tools



Holder tools



Multidiameter



RM solid compensation module

Stayplate

For detailed information, please visit roxtec.com.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied expressions and warranties provided by statute or

common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect,

consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from

https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/
We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-05-03

2/2 2024-05-03