



Roxtec SK BG™ transit

Transit for bonding and grounding with deep frame for angular attachment.

The Roxtec SK BG $^{\rm m}$ is a transit for bonding and grounding of armored and metal-clad cables and pipes. The transit frame has extended depth and is available in different materials and in a single or various combinations of openings. The metal frame is attached through welding and used for an angular attachment to accommodate stiff cables that do not pass in a straight angle through a deck or bulkhead. The seal allows for an increased distance between the packing space and the structure. The Roxtec BG $^{\rm m}$ sealing modules adapt to cables and pipes of different sizes and can be used to build in spare capacity in the seal. Roxtec EC (electrical continuity) test sticks are available to help indicate the electrical performance of the transit installation.





Easy to maintain and inspect

Product characteristics









Fire rate

Watertight

Gas-tigh

Electrical safet

Structure of installation



Meta


Mounting type




Welding

Ratings & certificates

Fire Tie





Tightness

Gas: 2.5 bar (catastrophic)

Water: 4 bar (catastrophic)

Supports



Bonding and grounding

Frame dimensions

in/lbs

The frame variants below are a limited selection. For the full range of frames and configurations, please visit roxtec.com.

Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
1	4.724 x 7.087	5.531 x 9.37 x 3.937	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	4	5SK0000004854
2	4.724 x 7.087	10.669 x 9.37 x 3.937	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	6.2	5SK0000010929
3	4.724 x 7.087	15.807 x 9.37 x 3.937	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	8.8	170071
1	4.724 x 7.087	5.531 x 9.37 x 3.937	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	11.5	5SK0000004397
2	4.724 x 7.087	10.669 x 9.37 x 3.937	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	18.3	5SK0000004504
3	4.724 x 7.087	15.807 x 9.37 x 3.937	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	24.3	5SK0000004399
1	4.724 x 7.087	5.531 x 9.37 x 3.937	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	11.7	5SK0000007066
2	4.724 x 7.087	10.669 x 9.37 x 3.937	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	19.9	5SK0000003590
3	4.724 x 7.087	15.807 x 9.37 x 3.937	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	25.9	5SK0000004198
	1 2 3 1 1 2 2 3 1 1 2 2	1 4.724 x 7.087 2 4.724 x 7.087 3 4.724 x 7.087 1 4.724 x 7.087 2 4.724 x 7.087 3 4.724 x 7.087 1 4.724 x 7.087 1 4.724 x 7.087 2 4.724 x 7.087	1 4.724 x 7.087 5.531 x 9.37 x 3.937 2 4.724 x 7.087 10.669 x 9.37 x 3.937 3 4.724 x 7.087 15.807 x 9.37 x 3.937 1 4.724 x 7.087 5.531 x 9.37 x 3.937 2 4.724 x 7.087 10.669 x 9.37 x 3.937 3 4.724 x 7.087 15.807 x 9.37 x 3.937 1 4.724 x 7.087 5.531 x 9.37 x 3.937 2 4.724 x 7.087 5.531 x 9.37 x 3.937 2 4.724 x 7.087 5.531 x 9.37 x 3.937 2 4.724 x 7.087 10.669 x 9.37 x 3.937	Wx HxD	WxHxD w x h Wx HxD w x h A.724 x 7.087 5.531 x 9.37 x 3.937 5.63(+0.039/-0.039) x 9.449(+0.039/-0.039) x 9.4

2024-05-01



https://www.roxtec.com/linktransit/en-nz/solution/18570



Sealing components

Sealing components



RM BG[™] module with Multidiameter



Lubricant



RM BG™ solid npensation module





Wedge & Wedgekit



Stayplate

Accessories



Accessories ES and BG



Holder tools



Welding tools

BG™ sealing kit

For detailed information, please visit roxtec.com.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

the intended process, installation and/or use.
Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.
Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect,

consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-05-01

2/2 2024-05-01