



Roxtec SK BG™ transit

Transit for bonding and grounding with deep frame for angular attachment.

The Roxtec SK BG™ is a transit for bonding and grounding of armored and metal-clad cables and pipes. The transit frame has extended depth and is available in different materials and in a single or various combinations of openings. The metal frame is attached through welding and used for an angular attachment to accommodate stiff cables that do not pass in a straight angle through a deck or bulkhead. The seal allows for an increased distance between the packing space and the structure. The Roxtec BG™ sealing modules adapt to cables and pipes of different sizes and can be used to build in spare capacity in the seal. Roxtec EC (electrical continuity) test sticks are available to help indicate the electrical performance of the transit installation.



- Easy to maintain and inspect

Product characteristics



Fire rated



Watertight



Gas-tight



Electrical safety

Structure of installation



Metal

Mounting type



Welding

Ratings & certificates

Fire

- A-CLASS according to IMO 2010 FTP Code
- H-CLASS according to IMO 2010 FTP Code + HC fire load curve

Tightness

- Gas: 2.5 bar (catastrophic)
- Water: 4 bar (catastrophic)

Supports

- Bonding and grounding

Frame dimensions

in/lbs

The frame variants below are a limited selection. For the full range of frames and configurations, please visit [roxtec.com](https://www.roxtec.com).

Product	Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
SK 6x1 ALU	1	4.724 x 7.087	5.531 x 9.37 x 3.937	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	3.97	5SK0000004854
SK 6x2 ALU	2	4.724 x 7.087	10.669 x 9.37 x 3.937	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	6.24	5SK0000010929
SK 6x3 ALU	3	4.724 x 7.087	15.807 x 9.37 x 3.937	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	8.82	170071
SK 6x1 PRIMED	1	4.724 x 7.087	5.531 x 9.37 x 3.937	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	11.46	5SK0000004397
SK 6x2 PRIMED	2	4.724 x 7.087	10.669 x 9.37 x 3.937	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	18.3	5SK0000004504
SK 6x3 PRIMED	3	4.724 x 7.087	15.807 x 9.37 x 3.937	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	24.25	5SK0000004399
SK 6x1 AISI316	1	4.724 x 7.087	5.531 x 9.37 x 3.937	5.63(+0.039/-0.039) x 9.449(+0.039/-0.039)	11.75	5SK0000007066
SK 6x2 AISI316	2	4.724 x 7.087	10.669 x 9.37 x 3.937	10.748(+0.039/-0.039) x 9.449(+0.039/-0.039)	19.89	5SK0000003590
SK 6x3 AISI316	3	4.724 x 7.087	15.807 x 9.37 x 3.937	15.906(+0.039/-0.039) x 9.449(+0.039/-0.039)	25.93	5SK0000004198




Sealing components


Sealing components



BG™ sealing kit



RM BG™ solid compensation module



RM BG™ module with Multidiameter™



Stayplate



Wedge & Wedge kit



Welding tools



Holder tools



Lubricant



ES and BG installations

For detailed information, please visit [roxtec.com](https://www.roxtec.com).

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2026-08-07



Roxtec ® and Multidiameter ® are registered trademarks of Roxtec in Sweden and/or other countries.