




Roxtec RS EMC seal

Penetration seal for EMC, for a single cable or pipe.

The Roxtec RS EMC is a seal for electromagnetic compatibility designed for single cables or pipes in metal sleeves. The entry seal has two halves with removable layers making it adaptable to cables and pipes of different sizes. There is a choice between the ES version for electromagnetic shielding and the PE version that protects against conducted disturbances. The design of the seal makes it easy to install around existing cables or pipes. Roxtec EC (electrical continuity) test sticks are available to help indicate the electrical performance of the transit installation.





Ratings & certificates

Fire

- Tightness
- Gas: 2.67 bar (catastrophic)
- Water: 4 bar (catastrophic)

Supports

- Electromagnetic shielding
- Potential equalization

Code

A-CLASS according to IMO 2010 FTP

- E/El rating according to EN 13501
- F/T rating according to UL 1479
- H-CLASS according to IMO 2010 FTP Code + HC fire load curve
- Jet fire according to ISO 22899-1 and OTI 95634

Sealing components


RS PE seal

Sealing components



Lubricant

For detailed information, please visit roxtec.com.



RS ES seal

Accessories



Accessories ES and BG





Pre-configured transit kits

in/lbs

RS 50 PE AISI316







RS 25 PE AISI316



RS 43 ES AISI316



RS 75 PE AISI316

RS 68 ES AISI316



RS 75 ES AISI316



RS 125 PE AISI316



RS 100 ES AISI316 RS 125 ES AISI316 WOC













Weight

0.71

Art. no

PRS0100501121

PRS0001501121

3.5



RS 100 PE AISI316 WOC



RS 125 PE AISI316 WOC

Product

RS 50 PE AISI316

RS 25 ES AISI316

RS 68 PE AISI316

RS 25 PE AISI316

RS 43 ES AISI316

RS 75 PE AISI316

RS 68 ES AISI316

RS 75 ES AISI316

RS 125 PE AISI316

RS 43 PE AISI316

RS 100 ES AISI316

RS 31 ES AISI316

RS 100 PE AISI316

RS 31 PE AISI316

RS 50 ES AISI316

RS 125 ES AISI316

RS 150 PE AISI316 WOC



RS 43 PE AISI316

RS 100 PE AISI316



RS 100 ES AISI316 WOC

RS 31 PE AISI316

Configuration

1x (0.315-1.181)

1x (3.661-4.685)



RS 50 ES AISI316




RS 125 ES AISI316

1.969 - 2.047



RS 150 PE AISI316 WOC

Aperture dimensions



5.906 - 5.984



Read more about the solution on roxtec.com

https://www.roxtec.com/linktransit/en-gb/solution/18575



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system was designed or intended. Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or consequential, punity, special, exemplary or incidental damages or losses. The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/ We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-27