




Roxtec RS EMC seal

The Roxtec RS EMC is a seal for electromagnetic compatibility designed for single cables or pipes in metal sleeves. The entry seal has two halves with removable layers making it adaptable to cables and pipes of different sizes. There is a choice between the ES version for electromagnetic shielding and the PE version that protects against conducted disturbances. The design of the seal makes it easy to install around existing cables or pipes. Roxtec EC (electrical continuity) test sticks are available to help indicate the electrical performance of the transit installation.



- Rodent resistant
- Quick and easy to install

Product characteristics













Mounting type

Structure of installation

Ratings & certificates

Fire

- A-CLASS according to IMO 2010 FTP
- E/EI rating according to EN 13501
- F/T rating according to UL 1479
- H-CLASS according to IMO 2010 FTP Code + HC fire load curve
- Jet fire according to ISO 22899-1 and OTI

Tightness

- Gas: 2.67 bar (catastrophic)
- Water: 4 bar (catastrophic)

Supports

- Electromagnetic shielding
- Potential equalization

Sealing components

Sealing components





RS PE seal



RS ES seal

Accessories



Accessories ES and BG

For detailed information, please visit roxtec.com.

2024-04-27





Pre-configured transit kits

in/lbs







RS 25 ES AISI316



RS 68 PE AISI316



RS 25 PE AISI316



RS 43 ES AISI316



RS 75 PE AISI316



RS 68 ES AISI316



RS 75 ES AISI316



RS 125 PE AISI316



RS 43 PE AISI316



RS 100 ES AISI316 WOC



RS 100 ES AISI316



RS 125 ES AISI316 WOC



RS 31 ES AISI316



RS 150 ES AISI316 WOC



RS 100 PE AISI316 WOC



RS 125 PE AISI316 WOC



RS 100 PE AISI316



RS 31 PE AISI316



RS 50 ES AISI316



RS 125 ES AISI316



RS 150 PE AISI316 WOC

Product	Configuration	Aperture dimensions ∅	Weight	Art. no
RS 50 PE AISI316	1x (0.315-1.181)	1.969 - 2.047	0.71	PRS0100501121
RS 25 ES AISI316	1x (0.142-0.472)	0.984 - 1.024	0.09	ERS0100251121
RS 68 PE AISI316	1x (1.024-1.890)	2.677 - 2.756	1.1	PRS0100681121
RS 25 PE AISI316	1x (0.142-0.472)	0.984 - 1.024	0.09	PRS0100251121
RS 43 ES AISI316	1x (0.157-0.906)	1.693 - 1.772	0.53	ERS0100431121
RS 75 PE AISI316	1x (0.945-2.126)	2.953 - 3.031	1.3	PRS0100751121
RS 68 ES AISI316	1x (1.024-1.890)	2.677 - 2.756	1.1	ERS0100681121
RS 75 ES AISI316	1x (0.945-2.126)	2.953 - 3.031	1.3	ERS0100751121
RS 125 PE AISI316	1x (2.598-3.858)	4.921 - 5	3.5	PRS0101251121
RS 43 PE AISI316	1x (0.157-0.906)	1.693 - 1.772	0.53	PRS0100431121
RS 100 ES AISI316 WOC	1x (1.890-2.756)	3.937 - 4.016	1.9	ERS0001001121
RS 100 ES AISI316	1x (1.890-2.756)	3.937 - 4.016	2.2	ERS0101001121
RS 125 ES AISI316 WOC	1x (2.598-3.858)	4.921 - 5	2.7	ERS0001251121
RS 31 ES AISI316	1x (0.157-0.669)	1.22 - 1.26	0.24	ERS0100311121
RS 150 ES AISI316 WOC	1x (3.661-4.685)	5.906 - 5.984	3.5	ERS0001501121
RS 100 PE AISI316 WOC	1x (1.890-2.756)	3.937 - 4.016	1.9	PRS0001001121
RS 125 PE AISI316 WOC	1x (2.598-3.858)	4.921 - 5	2.7	PRS0001251121
RS 100 PE AISI316	1x (1.890-2.756)	3.937 - 4.016	2.2	PRS0101001121
RS 31 PE AISI316	1x (0.157-0.669)	1.22 - 1.26	0.13	PRS0100311121
RS 50 ES AISI316	1x (0.315-1.181)	1.969 - 2.047	0.71	ERS0100501121
RS 125 ES AISI316	1x (2.598-3.858)	4.921 - 5	3.5	ERS0101251121
RS 150 PE AISI316 WOC	1x (3.661-4.685)	5.906 - 5.984	3.5	PRS0001501121

2/3 2024-04-27



Read more about the solution on roxtec.com

https://www.roxtec.com/linktransit/en-nz/solution/18575



The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-27

3/3 2024-04-27