



Roxtec S Ex transit

Ex rated transit for welding to the structure.

The Roxtec S Ex is a multi-cable and pipe transit rated for Ex e and Ex tb areas. The transit frame is available in different materials and with a single or various combinations of openings. The frame is produced in 10mm thick metal and is attached to the structure by welding. The Roxtec Ex sealing modules adapt to cables and pipes of different sizes and can be used to build in spare capacity in the seal.

Easy to maintain and inspect

Provides built-in spare capacity

Image: second pipesImage: second pipesProduct characteristicsImage: second pipesImage: sec

Ratings & certificates

Fire

- A-CLASS according to IMO 2010 FTP Code
- H-CLASS according to IMO 2010 FTP Code + HC fire load curve

	Tigł	ntness
--	------	--------

- Gas: 2.5 bar (catastrophic)
- Water: 4 bar (catastrophic)
-) IP 66/67

Supports

Bonding and grounding
Electromagnetic shielding
Potential equalization
Ex rated

Frame dimensions

in/lbs

W

The frame variants below are a limited selection. For the full range of frames and configurations, please visit roxtec.com.

f	Product	Frame openings	Packing space	External dimensions WxHxD	Aperture dimensions w x h	Weight	Art. no
	S 6x1 Ex PRIMED	1	4.724 x 7.087	5.551 x 9.37 x 2.362	5.63(-0.079) x 9.449	7.4	EXS006000000112
	S 6x1 Ex AISI316	1	4.724 x 7.087	5.551 x 9.37 x 2.362	5.63(-0.079) x 9.449	7.4	EXS006000000121
н	S 6x2 Ex PRIMED	2	4.724 × 7.087	10.669 x 9.37 x 2.362	10.748(-0.079) x 9.449	12.1	EXS00600000212
	S 6x2 Ex AISI316	2	4.724 × 7.087	10.669 x 9.37 x 2.362	10.748(-0.079) x 9.449	12.1	EXS00600000221
	S 6x3 Ex PRIMED	3	4.724 x 7.087	15.827 x 9.37 x 2.362	15.906(-0.079) x 9.449	17	EXS00600000312
	S 6x3 Ex AISI316	3	4.724 x 7.087	15.827 x 9.37 x 2.362	15.906(-0.079) x 9.449	17	EXS00600000321





Sealing components

Sealing components



Lubricant



Wedge & Wedgekit Ex



RM Ex solid compensation module



RM Ex module with

Multidiameter™





Stayplate Ex

Holder tools

Welding tools



RM BG[™] Ex module with

Multidiameter



RM BG™ Ex solid compensation module

RM ES Ex module with Multidiameter



compensation module



Ex sealing kit



BG™ Ex sealing kit

For detailed information, please visit roxtec.com.

- The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for
- The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use. Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system was designed or intended.
- The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from

We reserve the right to make charges to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright. This document was generated on: 2024-04-27