



Roxtec Rahmen B Ex

Durchführung mit Zulassung für explosionsgefährdete Bereiche mit flexiblem Rahmen für unterschiedliche Kombinationen.

Roxtec B Ex ist eine Durchführung für mehrere Kabel und Rohre mit Zulassung für Ex e- und Ex tb-Bereiche. Der zu öffnende Metallrahmen wird in verschiedenen Größen und Kombinationen zusammengeschraubt und dann in die Struktur eingegossen, entweder zur Nachrüstung um vorhandene Kabel oder Rohre oder für den Einsatz in Neubauten. Die Roxtec Ex-Dichtungsmodule sind an Kabel und Rohre verschiedener Größe anpassbar und bieten Reservekapazität für künftigen Bedarf.



- Perfekt für die Nachrüstung

Produkteigenschaften



Feuerhemmend



IP/UL NEMA



Ex- zertifiziert



EMI-Schutz

Aufbau der Installation



Schalt-
schränke
und
Gehäuse



Metall



Beton

Montagetyp



Verschrauben



Gießen

Klassifizierungen und Zertifikate

Feuer

- E/EI-Klassifizierung gemäß EN 13501
- F/T-Klassifizierung gemäß UL 1479

Dichtigkeit

- IP 54

Belege

- Potentialausgleich
- Ex- zertifiziert

Rahmenmaße

mm/kg

Die folgenden Rahmenvarianten zeigen eine begrenzte Auswahl. Das gesamte Angebot an Rahmen und Konfigurationen finden Sie unter [roxtec.com](https://www.roxtec.com).

Titel	Rahmenöffnungen	Belegraum	Außenabmessungen WxHxD	Öffnungsmaße w x h	Gewicht	Art. Nr.
B 6x1 B Ex GALV	1	120 x 180	200.5 x 298 x 60	146(+1/-1) x 243(+1/-1)	3.7	EXBBB0600000115
B 6x1 C Ex GALV	1	120 x 180	200.5 x 298 x 60	146(+1/-1) x 243(+1/-1)	3.6	EXBBC0600000115
B 6x2 B Ex GALV	2	120 x 180	329 x 298 x 60	274(+1/-1) x 243(+1/-1)	6.1	EXBBB0600000215
B 6x2 C Ex GALV	2	120 x 180	329 x 298 x 60	274(+1/-1) x 243(+1/-1)	5.9	EXBBC0600000215
B 6x3 B Ex GALV	3	120 x 180	457.5 x 298 x 60	403(+1/-1) x 243(+1/-1)	8.7	EXBBB0600000315
B 6x3 C Ex GALV	3	120 x 180	457.5 x 298 x 60	403(+1/-1) x 243(+1/-1)	8.6	EXBBC0600000315



Daten der Abdichtungskomponenten

Dichtkomponenten


Zubehör



Gleitmittel



Roxtec-Keil- und Keildichtungskit Ex



Roxtec-Modul RM Ex mit Multidiameter™




Roxtec-Füll- und Ausgleichsmodul RM Ex




Roxtec-Ankerscheibe Ex



Haltwerkzeuge



Roxtec-Modul RM PE Ex mit Multidiameter™



Roxtec-Füll- und Ausgleichsmodul RM PE Ex



Roxtec-Dichtungskit Ex

Weitere Informationen finden Sie unter www.roxtec.com.

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2024-04-20